

Spindle cable/Single core | TPE | chainflex® CFPE

36 10 million Double strokes guaranteed **7.5 x d** Bend radius, e-chain® **400m** Travel distance, e-chain®

- For extremely heavy duty applications
- TPE outer jacket
- Oil and bio-oil-resistant
- Flame-retardant
- UV-resistant
- Hydrolysis and microbe-resistant

Dynamic information

Bend radius	e-chain® linear	minimum 7.5 x d
	flexible	minimum 6 x d
	fixed	minimum 4 x d
Temperature	e-chain® linear	-35°C up to +90°C
	flexible	-45°C up to +90°C (following DIN EN 60811-504)
	fixed	-50°C up to +90°C (following DIN EN 50305)
v max.	unsupported	10m/s
a max.	gliding	6m/s
Travel distance	Unsupported travels and up to 400m and more for gliding applications, Class 6	
Torsion	Torsion ±90°, with 1m cable length, Class 2	

Cable structure

Conductor	Conductor cable consisting of pre-leads (following DIN EN 60228).
Core insulation	Mechanically high-quality TPE mixture.
Core identification	Green-yellow
Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®. Colour: Signal black (similar to RAL 9004)

Electrical information

Nominal voltage	600/1,000V (following DIN VDE 0298-3) 1,000V (following UL)
Testing voltage	4,000V (following DIN EN 50395)

Properties and approvals

UV resistance	High
Oil resistance	Oil-resistant (following DIN EN 60811-404), bio-oil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"

EPLAN download, configurators ► www.igus.eu/CFPE

36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

Class 6.6.4.2

UL/CSA AWM	See data sheet for details ► www.igus.eu/CFPEE
NFPA	Following NFPA 79-2018, chapter 12.9
DNV	Type Approval Certificate TAE00003XC
EAC	Certificate No. RU C-DE.ME77.B.00863/20
REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF34.UL.25.04.D - tested by IPA according to standard DIN EN ISO 14644-1 Following 2014/35/EU
CE	
UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-35/-25	10	11	12
-25/+80	7.5	8.5	9.5
+80/+90	10	11	12

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heavy-duty applications, Class 6
- Unsupported travels and up to 400m and more for gliding applications, Class 6
- Almost unlimited resistance to oil, also with bio-oils, Class 4
- Torsion ±90°, with 1m cable length, Class 2
- Indoor and outdoor applications, UV-resistant
- Storage and retrieval units for high-bay warehouses, machining units/machine tools, quick handling, cleanroom, semiconductor insertion, outdoor cranes, low-temperature applications

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFPE.15.01	1G1.5	4.5	16	31
CFPE.25.01	1G2.5	5.5	25	42
CFPE.40.01	1G4.0	6.0	41	59
CFPE.60.01	1G6.0	7.0	61	83
CFPE.100.01	1G10	7.5	100	124
CFPE.160.01	1G16	9.5	159	195
CFPE.250.01	1G25	11.5	248	294
CFPE.350.01	1G35	12.5	347	395
CFPE.500.01	1G50	14.5	495	551
CFPE.700.01	1G70	16.5	725	813
CFPE.950.01	1G95	20.0	936	1080

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Basic requirements	low	1	2	3	4	5	6	7	highest
Travel distance	unsupported	1	2	3	4	5	6	7	≥ 400m
Oil resistance	none	1	2	3	4	5	6	7	highest
Torsion	none	1	2	3	4	5	6	7	±360°

