



Order key for tubes

Type	Dimensions [mm]
SF T J -110 70- □	
<div style="display: flex; justify-content: space-between;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Bar stock</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Tube</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">iglidur® material</div> </div>	<div style="display: flex; justify-content: space-between;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Outer Ø</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Inner Ø</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Length</div> </div>

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

Inner Ø	Inner diameter tolerance	Outer Ø	Outer diameter tolerance	Length	Part No.
70	-2.0 / -6.5	110	+1.5 / +4.5	50 – 1,000	SFTJ-11070
70	-2.0 / -6.5	125	+1.5 / +4.5	50 – 1,000	SFTJ-12570
100	-2.0 / -6.5	150	+1.5 / +4.5	50 – 1,000	SFTJ-150100

Available from stock
Upon request/check availability



Order key for plate strips

Type	Dimensions [mm]
SF P □ -15-160- □	
<div style="display: flex; justify-content: space-between;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Bar stock</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Plate</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">iglidur® material</div> </div>	<div style="display: flex; justify-content: space-between;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Material thickness</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Width</div> <div style="writing-mode: vertical-rl; transform: rotate(180deg);">Length</div> </div>

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

iglidur® material	Material thickness s	Material thickness Tolerance	Width	Part No.
A500	15	+0.300 +1.500	160	SFPA500-15-160-□
A500	30	+0.500 +2.500	160	SFPA500-30-160-□
A500	50	+0.500 +3.500	160	SFPA500-50-160-□
C500	15	+0.300 +1.500	160	SFPC500-15-160-□
E7	30	+0.500 +2.500	160	SFPE7-30-160-□
HSD350	50	+0.500 +3.500	160	SFPHSD350-50-160-□
J350	15	+0.300 +1.500	160	SFPJ350-15-160-□
J4	15	+0.300 +1.500	160	SFPJ4-15-160-□
J4	30	+0.500 +2.500	160	SFPJ4-30-160-□
J4	50	+0.500 +3.500	160	SFPJ4-50-160-□
K230	15	+0.300 +1.500	160	SFPK230-15-160-□
RW370	15	+0.300 +1.500	160	SFPRW370-15-160-□
W300	15	+0.300 +1.500	160	SFPW300-15-160-□
X	15	+0.300 +1.500	160	SFPX-15-160-□

igus® constantly expands its range of available materials and dimensions. Please contact us in case the required diameter is not available.