

## 2. LOCAL DUST COLLECTORS (P-SERIES)

### 2.2.3. TYPE P1200/9/N

#### DESCRIPTION

- **box-shaped dust collector for the local dedusting - big-bags filling, welding and cutting machines etc.**

#### OPERATION QUALITIES

- air volume: 1800 m<sup>3</sup>/h
- filtration area: 35,6 m<sup>2</sup>
- fan: 2,2 kW, 3 x 400 V AC, 50 Hz
- rest concentration at the outlet: <10 mg/m<sup>3</sup>
- temperature resistance: -20 °C/+80 °C
- compressed air: max. 6 bar, air consumption 6 Nm<sup>3</sup>/h
- pressure loss: 1500 Pa
- weight: 400 kg

#### DESIGN

- carbon steel construction
- filter element: 9 x filter cartridge made of polyester in basic design diameter 145 mm, length 1200 mm
- air tank with JET-PULS filter cartridges recovery and timer
- compressed air inlet: internal thread G 1/2"
- pulse and safety valves, pressure regulator
- pressure switch to indicate the filter cartridges are plugged
- support frame with the dust container

#### ADDITIONAL ACCESSORIES

- electric control panel: 3 x 400 V AC, 50 Hz
- noise silencer
- dedusting arms
- ATEX design
- stainless steel version
- non-standard temperature design: -40 °C/+150 °C

#### BENEFITS

- robust design
- easy filter element replacement
- low dust emission level
- excellent access to every filter component



Dust collector type P1200/9/N with the support frame and dust container is used for the local filtration – dedusting of big-bags filling, welding and cutting machines etc.

## 2. LOCAL DUST COLLECTORS (P-SERIES) 2.2.3. TYPE P1200/9/N

