

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on stockpiles and ships

OPERATION QUALITIES

- max. loading rate 1500 m³/h (depends on particle size and product bulk density)
- particle size 0 - 300 mm
- inlet diameter DN 1000
- operating temperature -20 °C / +80 °C
- motor drive 11 - 15 kW
- loading conduit consisting of internal telescopic tubes and external bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 4 x tilt type
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- design for ATEX
- load cells to prevent the clogging
- non-standard temperature (-40 °C / +250 °C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
3 000	10 400	7 400	3 900
3 640	12 280	8 640	6 746
3 350	13 380	10 030	4 800
3 680	15 750	12 070	5 550
3 930	17 980	14 050	5 925
4 325	19 110	14 785	8 063



0 - 300



max. 1500 m³/h

Robust-design telescopic loading spout type NZO1000DH with the dustproof bell, rubber skirt and level switches guarantees you a dustless loading of dry, dusty bulk solids on stockpiles or ships.

