

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. flow rate 250 m³/h
- particle size 0-80 mm
- inlet diameter DN300
- pipe Ø125 mm for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drive 0.55 kW
- loading conduit consisting of internal cones and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – rotary / vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout
- available also with manual winch

ADDITIONAL ACCESSORIES

- electric control box
- pendant or remote control
- vibration unit
- shut off valves (manual, electro, pneumatic)
- design for ATEX / non-standard temperature (-40 °C/+250 °C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
1 300	3 300	2 000	145
1 400	3 900	2 500	156
1 500	4 500	3 000	167
1600	5100	3500	195
1 700	5 700	4 000	189
1 800	6 300	4 500	229
1 900	6 500	4 600	238
2 100	7 000	4 900	307



Telescopic loading spout type NZO300E with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on open trucks and railway cars.

