

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. loading rate 450-500 m³/h
- particle size 0-80 mm
- inlet diameter DN 500
- operating temperature -20 °C / +80 °C
- motor drive 1.25 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – rotary / vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- pendant or remote control
- vibration unit
- design for ATEX
- non-standard temperature (-40 °C/+250 °C)

L_{min} (retracted length)	L_{max} (extracted length)	Travel (H)	Weight
1400	3500	2100	565
1460	4000	2540	590
1600	4500	2900	620
1635	5160	3525	666
1775	5750	3975	692
1830	6200	4370	730



Telescopic loading spout type NZO500S with the dustproof bell, rubber skirt and level indicator guarantee you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

2.2. STANDARD LINE

2.2.2. NZO500S

