

Clevis joints with clevis pin and circlip:  
GERMK and GELMK



- Lightweight
- Absolute corrosion resistance
- High tensile force
- Can be combined with E series rod end

Order key

Type	Size [mm]	Options
<b>G E</b> □ <b>M K</b> - <b>04</b> <b>LS</b>		
<b>Clevis joint</b>	<b>E series</b>	<b>Thread</b>
	<b>Metric</b>	<b>Clevis pin and circlip</b>
	<b>Inner Ø</b>	
		Thread L = Left-hand thread R = Right-hand thread  Add-on: LS = Longer shank

**Material:**  
igumid G ► Page 1654

**Service life calculation online**  
► [www.igus.eu/igubal-expert](http://www.igus.eu/igubal-expert)

Technical data

Part No.	Max. static tensile strain		Max. static axial force		Weight [g]
	Short-term	Long-term	Short-term	Long-term	
	[N]	[N]	[N]	[N]	
GE□MK-04 M3.5	500	250	250	125	1.3
GE□MK-04	500	250	250	125	1.3
GE□MK-05 DIN M4	800	400	250	125	2.1
GE□MK-05 DIN M5	800	400	250	125	2.1
GE□MK-05	900	450	250	125	3.3
GE□MK-05 DIN M5 LS <sup>22)</sup>	800	400	130	65	2.9
GE□MK-06	1,300	650	300	150	3.3
GE□MK-06 LS <sup>22)</sup>	1,300	650	130	65	4.4
GE□MK-08	2,100	1,050	650	325	7.9
GE□MK-10	3,000	1,500	800	400	16.4
GE□MK-10 F	3,000	1,500	800	400	16.4
GE□MK-12	3,500	1,750	900	450	25.3
GE□MK-12 F	3,500	1,750	900	450	25.3
GE□MK-14	6,100	3,050	1,000	500	31.2
GE□MK-15	2,800	1,400	1,000	500	38.9
GE□MK-16	7,000	3,500	1,200	600	60.8
GE□MK-16 F	7,000	3,500	1,200	600	60.8
GE□MK-17	3,600	1,800	1,200	600	62.3
GE□MK-17 F	3,600	1,800	1,200	600	62.3
GE□MK-20	9,000	4,500	3,000	1,500	125.2
GE□MK-20 M20	9,000	4,500	3,000	1,500	125.2

<sup>22)</sup> LS = longer shank

**Single components: clevis pin GBM and circlip GSR**  
► Page 783

Clevis joints with spring-loaded fixing clip:  
GERMF and GELMF



- One-piece design
- Easy assembly/disassembly
- Easy assembly also for use in hard to reach locations
- Can be combined with E series rod end
- Corrosion-resistant and lightweight

Order key

Type	Size [mm]	Options
<b>G E</b> □ <b>M F</b> - <b>04</b> <b>LS</b>		
<b>Clevis joint</b>	<b>E series</b>	<b>Thread</b>
	<b>Metric</b>	<b>Spring-loaded fixing clip</b>
	<b>Inner Ø</b>	
		Thread L = Left-hand thread R = Right-hand thread  Add-on: LS = Longer shank

**Material:**  
igumid G ► Page 1654

**Service life calculation online**  
► [www.igus.eu/igubal-expert](http://www.igus.eu/igubal-expert)

Technical data

Part No.	Max. static tensile strain		Max. static axial force		Weight [g]
	Short-term	Long-term	Short-term	Long-term	
	[N]	[N]	[N]	[N]	
GE□MF-04 M3.5	500	250	250	125	1.3
GE□MF-04	500	250	250	125	1.3
GE□MF-05 DIN M4	800	400	250	125	2.3
GE□MF-05 DIN M5	800	400	250	125	2.3
GE□MF-05 DIN M5 LS <sup>22)</sup>	800	400	130	65	2.3
GE□MF-05	900	450	250	125	3.8
GE□MF-06	1,300	650	300	150	3.9
GE□MF-06 LS <sup>22)</sup>	1,300	650	130	65	3.9
GE□MF-08	2,100	1,050	650	325	9.1
GE□MF-10	3,000	1,500	800	400	18.2
GE□MF-10 F	3,000	1,500	800	400	18.2
GE□MF-12	3,500	1,750	900	450	28.6
GE□MF-12 F	3,500	1,750	900	450	28.6
GE□MF-16	7,000	3,500	1,200	600	61.8
GE□MF-16 F	7,000	3,500	1,200	600	61.8

<sup>22)</sup> LS = longer shank

**Single components: Spring-loaded fixing clip GEFM**  
► Page 782