

# Control cable | iguPUR | chainflex® CF891

- 36** 5,000,000 Double strokes guaranteed
- 12.5 x d** Bend radius, e-chain®
- 10m** Travel distance, e-chain®

- For flexing applications
- iguPUR outer jacket
- Oil-resistant
- Shielded
- Flame-retardant

### Dynamic information

Bend radius	<b>e-chain® linear</b>	minimum 12.5 x d
	<b>flexible</b>	minimum 10 x d
	<b>fixed</b>	minimum 7 x d
Temperature	<b>e-chain® linear</b>	-20°C up to +80°C
	<b>flexible</b>	-40°C up to +80°C (following DIN EN 60811-504)
	<b>fixed</b>	-50°C up to +80°C (following DIN EN 50305)
v max.	<b>unsupported</b>	3m/s
a max.		20m/s²
Travel distance		Unsupported travels up to 10m, Class 1

### Cable structure

Conductor	Conductor consisting of bare copper wires (according to DIN EN 60228).
Core insulation	Mechanically high-quality TPE mixture.
Core structure	Cores wound with an optimised pitch length.
Core identification	Black cores with white numbers, one green-yellow core.
Overall shield	Braiding made of tinned copper wires. Coverage approx. 60% optical
Outer jacket	Low-adhesion iguPUR mixture, adapted to suit the requirements in e-chains®. Colour: jet black (similar to RAL 9005)

### Electrical information

Nominal voltage	300/500V 600V (following UL)
Testing voltage	2,000V (following DIN EN 50395)

Basic requirements  
Travel distance  
Oil resistance  
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

## Class 3.1.3.1

### Properties and approvals

UV resistance	Medium
Oil resistance	Oil-resistant (following DIN EN 50363-10-2), Class 3
Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
UL/CSA AWM	See data sheet for details ► <a href="http://www.igus.eu/CF891">www.igus.eu/CF891</a>
EAC	Certificate No. RU C-DE.ME77.B.00300/19
REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
CE	Following 2014/35/EU
UK CA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

### Guaranteed service life (details see page 28-29)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-20/-10	15	16	17
-10/+70	12.5	13.5	14.5
+70/+80	15	16	17

\* Higher number of double strokes? Service life calculation online ► [www.igus.eu/chainflexlife](http://www.igus.eu/chainflexlife)

### Typical application areas

- For flexing applications, Class 3
- Especially for unsupported travels, Class 1
- With influence of oil, Class 3
- No torsion, Class 1
- Indoor and outdoor applications without direct sun radiation
- Machining units/machine tools, low temperature applications



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year





igus® chainflex® CF891

Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF891.05.02	(2x0.5)C	6.0	18	37
CF891.05.03	(3G0.5)C	6.0	28	45
CF891.05.05	(5G0.5)C	7.0	41	62
CF891.05.12	(12G0.5)C	9.0	91	122
CF891.05.18	(18G0.5)C	11.0	136	174
CF891.05.25	(25G0.5)C	13.0	210	234
CF891.07.02	(2x0.75)C	6.5	30	48
CF891.07.03	(3G0.75)C	7.0	37	63
CF891.07.04	(4G0.75)C	7.5	46	68
CF891.07.05	(5G0.75)C	8.0	61	85
CF891.07.07	(7G0.75)C	9.0	83	109
CF891.07.12	(12G0.75)C	10.5	124	166
CF891.07.18	(18G0.75)C	12.0	183	232
CF891.07.25	(25G0.75)C	14.5	222	299
CF891.10.02	(2x1.0)C	6.5	30	50
CF891.10.03	(3G1.0)C	7.0	46	71
CF891.10.04	(4G1.0)C	7.5	63	98
CF891.10.05	(5G1.0)C	8.0	76	105
CF891.10.07	(7G1.0)C	9.5	100	126
CF891.10.12	(12G1.0)C	11.5	167	224
CF891.10.18 <sup>11)</sup>	(18G1.0)C	13.0	213	276
CF891.10.25	(25G1.0)C	16.0	291	382
CF891.15.02	(2x1.5)C	7.5	60	69
CF891.15.03	(3G1.5)C	7.5	63	85
CF891.15.04	(4G1.5)C	8.5	90	108
CF891.15.05	(5G1.5)C	9.0	94	129
CF891.15.07	(7G1.5)C	11.0	153	177
CF891.15.12	(12G1.5)C	13.0	212	276
CF891.15.25 <sup>11)</sup>	(25G1.5)C	18.5	425	560
CF891.25.04	(4G2.5)C	10.0	141	157
CF891.25.05	(5G2.5)C	11.0	149	192
CF891.25.07	(7G2.5)C	13.0	204	255

<sup>11)</sup> Phase-out model

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.  
G = with green-yellow earth core x = without earth core

### Class 3.1.3.1

Order example: **CF891.05.02** - to your desired length (0.5m steps)  
CF891 chainflex® series .05 Code nominal cross section .02 Number of cores

Order online ► [www.igus.eu/CF891](http://www.igus.eu/CF891)

Delivery time 24hrs or today.  
Delivery time means time until goods are shipped.



#### Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: [www.igus.eu/cf-case](http://www.igus.eu/cf-case)



chainflex® CF891 in an adjustment device for a process crane

EPLAN download, configurators ► [www.igus.eu/CF891](http://www.igus.eu/CF891)

