

Data cable | PUR | chainflex® CFROBOT3







36 10 million
Cycles guaranteed

10 x d
Bend radius, e-chain®







±180°/m
Torsion angle

- For torsion applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- Notch-resistant
- Hydrolysis and microbe-resistant



Dynamic information

| | | |
|--|--|--|
|  Bend radius | flexible twisted | minimum 10 x d |
| | fixed | minimum 5 x d |
|  Temperature | flexible twisted | -25°C up to +80°C |
| | fixed | -50°C up to +80°C (following DIN EN 50305) |
|  v max. | twisted | 180°/s |
|  a max. | twisted | 60°/s ² |
|  Travel distance | Robots and 3D movements, Class 1 | |
|  Torsion | Torsion ±180°, with 1m cable length, Class 3 | |






Cable structure

| | |
|--|--|
|  Conductor | Stranded conductor in especially bending-resistant version consisting of bare copper wires (following DIN EN 60228). |
|  Core insulation | Mechanically high-quality TPE mixture. |
|  Core structure | Cores twisted in pairs with a short pitch length, core pairs then wound with short pitch lengths. |
|  Core identification | Colour code in accordance with DIN 47100. |
|  Overall shield | Extremely torsion-resistant tinned wound copper shield. Coverage approx. 85% optical |
|  Outer jacket | Low-adhesion, halogen-free, highly abrasion resistant PUR mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-10-2) Colour: Steel blue (similar to RAL 5011) |

Electrical information










| | |
|--|--|
|  Nominal voltage | 300/500V (following DIN VDE 0298-3) 300V (following UL) |
|  Testing voltage | 2,000V (following DIN EN 50395) |

Properties and approvals

| | |
|--|--|
|  UV resistance | High |
|  Oil resistance | Oil-resistant (following DIN EN 50363-10-2), Class 3 |
|  Flame-retardant | According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame |
|  Silicone-free | Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992) |
|  Halogen-free | Following DIN EN 60754 |

| | | | | | | | | | |
|--------------------|-------------|---|---|---|---|---------|---|--------|---------|
| Basic requirements | low | 1 | 2 | 3 | 4 | 5 | 6 | 7 | highest |
| Travel distance | unsupported | 1 | 2 | 3 | 4 | 5 | 6 | ≥ 400m | |
| Oil resistance | none | 1 | 2 | 3 | 4 | highest | | | |
| Torsion | none | 1 | 2 | 3 | 4 | ±360° | | | |

Class 6.1.3.3

-  UL verified
-  UL/CSA AWM
-  NFPA
-  EAC
-  REACH
-  RoHS Lead-free
-  Cleanroom
-  CE
-  UKCA

Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
See data sheet for details ► www.igus.eu/CFROBOT3

Following NFPA 79-2018, chapter 12.9

Certificate No. RU C-DE.ME77.B.00300/19

In accordance with regulation (EC) No. 1907/2006 (REACH)

Following 2011/65/EC (RoHS-II/RoHS-III)

According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
Following 2014/35/EU

In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

| Cycles* | 5 million | 7.5 million | 10 million |
|---------------------------|--------------------|--------------------|--------------------|
| Temperature, from/to [°C] | Torsion max. [°/m] | Torsion max. [°/m] | Torsion max. [°/m] |
| -25/-15 | ±150 | ±90 | ±30 |
| -15/+70 | ±180 | ±120 | ±60 |
| +70/+80 | ±150 | ±90 | ±30 |

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heaviest duty applications with torsion movements, Class 6
- Especially for robots and 3D movements, Class 1
- Almost unlimited resistance to oil, Class 3
- Torsion ±180°, with 1m cable length, Class 3
- Indoor and outdoor applications, UV-resistant
- Robots, handling, spindle drives

| Part No. | Number of cores and conductor nominal cross section [mm ²] | Outer diameter (d) max. [mm] | Copper index [kg/km] | Weight [kg/km] |
|----------------------------------|--|------------------------------|----------------------|----------------|
| CFROBOT3.02.03.02 | (3x(2x0.25))C | 9.0 | 33 | 84 |
| CFROBOT3.02.04.02 | (4x(2x0.25))C | 10.5 | 38 | 103 |
| CFROBOT3.02.06.02 | (6x(2x0.25))C | 11.5 | 52 | 127 |
| CFROBOT3.02.08.02 ¹¹⁾ | (8x(2x0.25))C | 13.5 | 66 | 170 |
| CFROBOT3.05.05.02 | (5x(2x0.5))C | 12.5 | 80 | 170 |

¹¹⁾ Phase-out model

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



Example image

