

DESCRIPTION

telescopic loading spout for dust-free loading of abrasive, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. flow rate 1300 m³/h
- particle size 0-100 mm
- inlet diameter DN 800
- operating temperature -20 °C / +80 °C
- motor drive 2.2 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 2 x rotary / 2 x vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- vibration unit
- design for ATEX
- non-standard temperature (-40 °C / +250 °C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
2420	6000	3580	1825
2540	6700	4160	1885
2640	7200	4560	1940
2740	7800	5060	1990



0 - 100



max. 1300 m³/h

Robust-design telescopic loading spout type NZO800H with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, abrasive bulk solids on trucks or railway cars.

2.3. HEAVY LINE

2.3.2. NZO800H

