


Low pressure tongue-type nozzles
Series 684



Features:


- Sharply delimited, powerful flat fan spray
- Large spray angle
- Assembly with retaining nut
- Non-clogging

Applications:

- Foam control
- Cleaning processes
- Washing processes



Series 684




G	Dimensions [mm]			Weight [g]
	L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSP	2.00	14.80	12.65	3.00

Spray angle	η	Ordering no.			Color ¹	Bore diameter B [mm]	L ₁ [mm]	V̇ water [l/min]			Spray width B [mm] (at p = 2 bar) 
		Type	Mat. no.					p [bar]			
			56	5E							
			POM	PVDF				1.0	2.0	5.0	H = 250 [mm]
140°	75°	684.348	●		Green	0.70	20.00	0.35*	0.50	0.79	1,240
		684.368	●	●	Yellow	0.80	20.00	0.45*	0.63	1.00	1,250
		684.408	●		Blue	1.00	20.00	0.71	1.00	1.58	1,260
		684.448	●		Red	1.20	20.00	0.88	1.25	1.98	1,260
		684.488	●	●	Brown	1.30	20.00	1.13	1.60	2.53	1,270
		684.528	●		Grey	1.50	20.00	1.41	2.00	3.16	1,280
		684.568	●	●	White	1.70	19.00	1.77	2.50	3.95	1,290
		684.608	●		Light blue	1.90	19.00	2.23	3.15	4.98	1,300
		684.688	●		Green	2.40	17.00	3.54	5.00	7.91	1,330
		684.728	●	●	Black	2.70	17.00	4.45	6.30	9.96	1,340
		684.808	●		Beige	3.40	16.00	7.07	10.00	15.81	1,340

* Differing spray pattern.

¹ PVDF material is always blue.

Assembly example



Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 684.348 + 56 = 684.348.56



Assembly accessories can be found in Chapter 9 "Accessories".