

Data cable | TPE | chainflex® CF11



12.5 million
Double strokes guaranteed



6.8 x d
Bend radius, e-chain®



400m
Travel distance, e-chain®

- For extremely heavy duty applications
- TPE outer jacket
- Shielded
- Twisted pair
- Oil and bio-oil-resistant
- PVC and halogen-free
- Hydrolysis and microbe-resistant

**Now available
with UL approval
& 25% longer
service life**

Dynamic information

Bend radius	e-chain® linear	minimum 6.8 x d
	flexible	minimum 5 x d
	fixed	minimum 4 x d
Temperature	e-chain® linear	-35°C up to +100°C
	flexible	-50°C up to +100°C (following DIN EN 60811-504)
	fixed	-55°C up to +100°C (following DIN EN 50305)
v max.	unsupported	10m/s
	gliding	6m/s
a max.		100m/s ²
Travel distance		Unsupported travels and up to 400m and more for gliding applications, Class 6

Cable structure

Conductor	Stranded conductor in especially bending-resistant version consisting of bare copper wires (following DIN EN 60228).
Core insulation	Mechanically high-quality TPE mixture.
Core structure	Cores twisted in pairs with a short pitch length, core pairs then wound with short pitch lengths.
Core identification	Cores < 1.0mm² : Colour code in accordance with DIN 47100. Cores ≥ 1.0mm² : Black cores with white numbers.
Inner jacket	TPE mixture adapted to suit the requirements in e-chains®.
Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®. Colour: Steel blue (similar to RAL 5011)

Electrical information

Nominal voltage	300/300V (following DIN VDE 0298-3) 300V (following UL)
Testing voltage	1,500V (following DIN EN 50395)

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Class 6.6.4.1

Properties and approvals

UV resistance	High
Oil resistance	Oil-resistant (following DIN EN 60811-404), bio-oil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
Halogen-free	Following DIN EN 60754
UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
UL AWM	See data sheet for details ► www.igus.eu/CF11 (from production date 01/2022)
EAC	Certificate No. RU C-DE.ME77.B.00300/19
REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF9.15.07 - tested by IPA according to standard DIN EN ISO 14644-1
CE	Following 2014/35/EU
UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

Double strokes*	5 million	7.5 million	12.5 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-35/-25	7.5	8.5	9.5
-25/+90	6.8	7.5	8.5
+90/+100	7.5	8.5	9.5

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heavy-duty applications, Class 6
- Unsupported travels and up to 400m and more for gliding applications, Class 6
- Almost unlimited resistance to oil, also with bio-oils, Class 4
- No torsion, Class 1
- Indoor and outdoor applications, UV-resistant
- Storage and retrieval units for high-bay warehouses, machining units/machine tools, quick handling, cleanroom, semiconductor insertion, outdoor cranes, low-temperature applications



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



Example image

EPLAN download, configurators ► www.igus.eu/CF11

36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

EU2023



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			



Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF11.01.04.02	(4x(2x0.14))C	7.5	30	63
CF11.01.18.02	(18x(2x0.14))C	12.5	101	202
CF11.02.01.02	(2x0.25)C	6.0	17	39
CF11.02.02.02 ²⁾	(2x(2x0.25))C	6.5	26	47
CF11.02.03.02	(3x(2x0.25))C	8.0	35	78
CF11.02.04.02	(4x(2x0.25))C	8.5	42	90
CF11.02.05.02	(5x(2x0.25))C	9.0	49	100
CF11.02.06.02	(6x(2x0.25))C	10.0	69	125
CF11.02.10.02	(10x(2x0.25))C	13.5	103	207
CF11.02.14.02	(14x(2x0.25))C	14.0	124	228
CF11.03.08.02	(8x(2x0.34))C	13.0	106	209
CF11.05.04.02	(4x(2x0.5))C	9.5	77	140
CF11.05.06.02	(6x(2x0.5))C	12.0	103	198
CF11.05.08.02	(8x(2x0.5))C	14.5	135	251
CF11.07.03.02	(3x(2x0.75))C	10.5	83	155
CF11.10.04.02	(4x(2x1.0))C	12.5	125	232
CF11.15.06.02	(6x(2x1.5))C	16.5	247	420

The chainflex® types marked with ²⁾ are cables designed as a star-quad.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



Class 6.6.4.1



Order example: CF11.01.04.02 - to your desired length (0.5m steps)

CF11 chainflex® series .01 Code nominal cross section .04 Number of cores .02 Identification pairs



Order online ► www.igus.eu/CF11



Delivery time 24hrs or today.

Delivery time means time until goods are shipped.

cost down...



...life up

Reduce cost, improve technology, now!

Do the chainflex® price check ...

www.igus.eu/cf-price-check

... for example: *reduce cost with CF211.PUR ...*



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year