

Measuring system cable | **PUR** | chainflex® CF113.D

**36** 10 million
Double strokes guaranteed

**7.5 x d**
Bend radius, e-chain®

**100m**
Travel distance, e-chain®

- For extremely heavy duty applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- Notch-resistant
- Hydrolysis and microbe-resistant

DriveCliqu with
300V UL approval

Dynamic information

	Bend radius	e-chain® linear	minimum 7.5 x d
		flexible	minimum 6 x d
		fixed	minimum 4 x d
	Temperature	e-chain® linear	-25°C up to +80°C
		flexible	-40°C up to +80°C (following DIN EN 60811-504)
		fixed	-50°C up to +80°C (following DIN EN 50305)
	v max.	unsupported	10m/s
		gliding	5m/s
	a max.		50m/s²
	Travel distance	Unsupported travels and up to 100m for gliding applications, Class 5	

Cable structure

	Conductor	Stranded conductor in especially bending-resistant version consisting of tinned copper wires (following DIN EN 60228).
	Core insulation	Mechanically high-quality TPE mixture.
	Core structure	According to measuring system specification.
	Core identification	According to measuring system specification. ► Product orange table
	Element shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Element shield	TPE mixture on pair shielding adapted to suit the requirements in e-chains®.
	Inner jacket	TPE mixture adapted to suit the requirements in e-chains®.
	Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer jacket	Low-adhesion, halogen-free, highly abrasion resistant PUR mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-10-2) Colour: Yellow-green (similar to RAL 6018)
	CFRIP®	Strip cables faster: a tear strip is moulded into the inner jacket Video ► www.igus.eu/CFRIP

Electrical information

	Nominal voltage	50V 300V (following UL)
	Testing voltage	500V

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Class 6.5.3.1

Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (following DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant following NEK 606 - status 2016
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	Halogen-free	Following DIN EN 60754
	UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	See data sheet for details ► www.igus.eu/CF113D
	NFPA	Following NFPA 79-2018, chapter 12.9
	DNV	Type Approval Certificate TAE00003X4
	EAC	Certificate No. RU C-DE.ME77.B.00295/19
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
	DESINA	According to VDW, DESINA standardisation
	CE	Following 2014/35/EU
	UK CA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-25/-15	10	11	12
-15/+70	7.5	8.5	9.5
+70/+80	10	11	12


* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heavy-duty applications, Class 6
- Unsupported travels and up to 100m for gliding applications, Class 5
- Almost unlimited resistance to oil, Class 3
- No torsion, Class 1
- Indoor and outdoor applications without direct sun radiation
- Storage and retrieval units for high-bay warehouses, machining units/machine tools, quick handling, cleanroom, semiconductor insertion, indoor cranes, low temperature applications



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified



Example image



EU2023

EU2023

Measuring system cable | PUR | chainflex® CF113.D

Strip cables 50% faster with CFRIP® tear strip

igus® chainflex® CF113.D

Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF113.001.D	(3x(2x0.14)C+(4x0.14)+(2x0.5))C	10.0	71	137
CF113.002.D	(3x(2x0.14)C+2x(0.5)C)C	10.0	74	144
CF113.003.D	(3x(2x0.14)+2x1.0)C	8.0	56	103
CF113.004.D	(2x(2x(2x0.14)))+(4x0.14)C+(4x0.5))C	11.0	78	152
CF113.005.D	(4x(2x0.14)+4x0.5)C	9.0	60	115
CF113.006.D	(3x(2x0.14)C+(4x0.14)+(4x0.25)+(2x0.5))C	11.0	85	158
CF113.007.D ²⁾	(4x0.34)C	6.5	31	54
CF113.008.D	(3x(2x0.25))C	7.5	36	76
CF113.009.D	(4x(2x0.25)+2x0.5)C	8.5	57	99
CF113.010.D	(4x(2x0.25)+2x1.0)C	9.0	68	122
CF113.011.D	(4x(2x0.34)+4x0.5)C	10.0	81	142
CF113.013.D	(3x(2x0.14)C+2x0.5)C	9.0	62	121
CF113.014.D	(4x(2x0.25)C+(2x0.5))C	11.0	86	163
CF113.015.D	(4x(2x0.14)+4x0.5)C	9.0	60	114
CF113.016.D	(3x(2x0.25)C)C	10.0	60	126
CF113.017.D ⁴⁾	(4x(2x0.14)+(4x0.14)C+4x1.0)C	10.0	100	150
CF113.018.D ⁴⁾	(2x(2x0.25)+2x0.5)C	6.5	41	65

The chainflex® types marked with ²⁾ are cables designed as a star-quad.

⁴⁾ Manufactured without inner jacket

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Guarantee
igus chainflex
36

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year

CFRIP®
igus chainflex

UL
US

UL
US

nec
NEPS

NFPA

CUPA

DNV
DNVGL

EAC

REACH

RoHS

clean-room

DESINA

CE

UK
CA

Class 6.5.3.1

Part No.	Core group	Colour code
CF113.001.D	3x(2x0.14)C (4x0.14) (2x0.5)	green/yellow, black/brown, red/orange grey/blue/white-yellow/white-black brown-red/brown-blue
CF113.002.D	3x(2x0.14)C 2x(0.5)C	green/yellow, black/brown, red/orange black, red
CF113.003.D	3x(2x0.14) 2x1.0	white/brown, green/yellow, grey/pink blue, red
CF113.004.D	2x(2x(2x0.14)) (4x0.14)C (4x0.5)	(brown/green)/(yellow/violet), (grey/pink)/(red/black) yellow-black/red-black/green-black/blue-black brown-green/white-green/blue/white
CF113.005.D	4x(2x0.14) 4x0.5	white/brown, green/yellow, grey/pink, blue/red black, violet, grey-pink, red-blue
CF113.006.D	3x(2x0.14)C (4x0.14) (4x0.25) (2x0.5)	green/yellow, black/brown, red/orange grey/blue/white-yellow/white-black yellow-brown/grey-brown/green-black/green-red brown-red/brown-blue
CF113.007.D ²⁾	4x0.34	white, green, brown, yellow (star-quad)
CF113.008.D	3x(2x0.25)	white/brown, green/yellow, grey/pink
CF113.009.D	4x(2x0.25) 2x0.5	brown/green, blue/violet, grey/pink, red/black white, brown
CF113.010.D	4x(2x0.25) 2x1.0	brown/green, blue/violet, grey/pink, red/black white, brown
CF113.011.D	4x(2x0.34) 4x0.5	black/brown, red/orange, green/yellow, blue/violet black-white, red-white, yellow-white, blue-white
CF113.013.D	3x(2x0.14)C 2x0.5	white/brown, green/yellow, grey/pink blue, red
CF113.014.D	4x(2x0.25)C (2x0.5)	white/brown, green/yellow, grey/pink, blue/red black no. 1/black no. 2
CF113.015.D	(4x(2x0.15))C 4x0.5	brown/green, yellow/violet, grey/pink, red/black blue, white, brown-green, white-green
CF113.016.D	3x(2x0.25)C	white/brown, green/yellow, grey/pink
CF113.017.D ⁴⁾	4x(2x0.14) (4x0.14)C 4x1.0	red/black, brown/green, yellow/violet, grey/pink blue-black/yellow-black/red-black/green-black white-green, brown-green, blue, white
CF113.018.D ⁴⁾	2x(2x0.25) 2x0.5	red/black, grey/pink white, brown

Further cable types ► Page 266

Measuring system cable | PUR | chainflex® CF113.D

Strip cables 50% faster with CFRIP® tear strip

igus® chainflex® CF113.D

Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF113.019.D ⁴⁾	(3x(2x0.25)C+(3x0.25)+2x1.0)C	10.0	93	143
CF113.022.D	((2x0.25)+5x0.5)C	8.0	54	94
CF113.025.D	(3x(2x0.14)C+(2x0.5)C)C	10.0	72	141
CF113.027.D	(5x(2x0.14)+2x0.5)C	9.0	52	105
CF113.028.D ⁴⁾	(2x(2x0.20)+(2x0.38))C	7.5	44	69
CF113.029.D	(5x(2x0.25)C+(2x0.25+2x0.5)C	12.0	105	192
CF113.031.D	(2x(2x0.25)C+2x1.0)C	9.5	69	133
CF113.032.D ⁵⁾	3x(2x0.14)C+(3x0.14)C	8.5	35	82
CF113.033.D ⁵⁾	4x(2x0.14)C+2x(1.0)C	9.5	64	111
CF113.036.D	(5x(2x0.25))C	8.5	51	103
CF113.037.D	(6x(2x0.25))C	9.0	58	114
CF113.038.D	(3x(2x0.14)+(2x0.34))C	8.5	36	87
CF113.040.D	(3x(4x0.14)+(2x0.14+2x0.34)+2x1.5)C	10.0	88	155

⁴⁾ Manufactured without inner jacket
⁵⁾ Manufactured without overall shield

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Further cable types ► Page 264



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



EPLAN download, configurators ► www.igus.eu/CF113D

Class 6.5.3.1

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Guarantee
igus chainflex
36

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year

CFRIP
igus chainflex

UL
US

CE
US

nec
NFPA

NFPA

CUPA

DNV

EAC

REACH

RoHS

clean-room

DESINA

CE

UK
CA

Part No.	Core group	Colour code
CF113.019.D ⁴⁾	3x(2x0.25)C (3x0.25) 2x1.0	brown/green, grey/pink, red/black blue/violet/yellow white, brown
CF113.022.D	(2x0.25) 5x0.5	white/brown green, yellow, grey, pink, blue
CF113.025.D	3x(2x0.14)C (2x0.5)C	green/yellow, blue/red, grey/pink white/brown
CF113.027.D	5x(2x0.14) 2x0.5	brown/green, yellow/grey, white/violet, red/black, pink/blue white-green, white-red
CF113.028.D ⁴⁾	2x(2x0.20) (2x0.38)	green/yellow, pink/blue red/black
CF113.029.D	5x(2x0.25)C (2x0.25+2x0.5)	white/brown green/yellow, grey/pink, blue/red, black/violet grey-pink/brown-green/white-green/red-blue
CF113.031.D	2x(2x0.25)C 2x1.0	white/brown, green/yellow black no. 1, black no. 2
CF113.032.D ⁵⁾	3x(2x0.14)C (3x0.14)C	green/black, yellow/black, red/black grey/pink/black
CF113.033.D ⁵⁾	4x(2x0.14)C 2x(1.0)C	yellow/black, red/black, blue/black, green/black white, brown
CF113.036.D	5x(2x0.25)	white/brown green/yellow, grey/pink, blue/red, black/violet
CF113.037.D	6x(2x0.25)	white/brown, green/yellow, grey/pink, blue/red, black/violet, grey-pink/red-blue
CF113.038.D	3x(2x0.14) (2x0.34)	white/brown, green/yellow, grey/pink blue/red
CF113.040.D	3x(4x0.14) (2x0.14+2x0.34) 2x1.5	black/red/white-black/white-red, green/blue/white-green/white-blue, yellow/brown/white-yellow/white-brown violet/orange/weißviolet/weißorange white-grey, grey



chainflex® measuring system cables in a double-spindle machining centre.

Guarantee
igus chainflex
36
up to 36 months guarantee

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

266 36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

EU2023



267