

Servo cable | PVC | chainflex® CF210.UL

36

10 million

Double strokes guaranteed

10 x d

Bend radius, e-chain®

10m

Travel distance, e-chain®

- For medium duty applications
 - PVC outer jacket
 - Shielded
 - Oil-resistant
- Flame-retardant

Dynamic information

	Bend radius	e-chain® linear	minimum 10 x d
		flexible	minimum 8 x d
		fixed	minimum 5 x d
	Temperature	e-chain® linear	+5°C up to +70°C
		flexible	-5°C up to +70°C (following DIN EN 60811-504)
		fixed	-15°C up to +70°C (following DIN EN 50305)
	v max.	unsupported	10m/s
	a max.	gliding	2m/s
	Travel distance	Unsupported travels and up to 10m for gliding applications, Class 2	

Cable structure

	Conductor	Stranded conductor in bending-resistant version consisting of bare copper wires (following DIN EN 60228).	
	Core insulation	Mechanically high-quality, especially low-capacitance XLPE mixture.	
	Core structure	Power cores and control pair elements wound with a short pitch length around a high tensile strength centre element.	
	Core identification	Power cores: Black cores with white numbers, one green-yellow core. 1. Core: U / L1 / C / L+ 2. Core: V / L2 3. Core: W / L3 / D / L- 1 control pair: Black cores with white numbers. 1. Control core: 4 2. Control core: 5 2 control pairs: Black cores with white numbers. 1. Control core: 5 2. Control core: 6 3. Control core: 7 4. Control core: 8	
	Element shield	Bending-resistant braiding made of tinned copper wires.	
	Intermediate layer	Foil taping over the outer layer.	
	Overall shield	Bending-resistant braiding made of tinned copper wires. Coverage linear approx. 55%, optical approx. 80%	
	Outer jacket	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-4-1). Colour: Pastel orange (similar to RAL 2003)	

EPLAN download, configurators ► www.igus.eu/CF210UL

36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

EU2023



Class 4.2.2.1

Electrical information

	Nominal voltage	600/1,000V (following DIN VDE 0298-3) 1,000V (following UL)
	Testing voltage	4,000V (following DIN EN 50395)

Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (following DIN EN 50363-4-1), Class 2
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	See data sheet for details ► www.igus.eu/CF210UL
	NFFPA	Following NFPA 79-2018, chapter 12.9
	EAC	Certificate No. RU C-DE.ME77.B.00863/20
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1 Following 2014/35/EU
	CE	In accordance with the valid regulations of the United Kingdom (as at 08/2021)
	UKCA	

Guaranteed service life (details see page 28-29)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	12.5	13.5	14.5
+15/+60	10	11	12
+60/+70	12.5	13.5	14.5

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For medium duty applications, Class 4
- Unsupported travels and up to 10m for gliding applications, Class 2
- Light oil influence, Class 2
- No torsion, Class 1
- Preferably indoor applications, but also outdoor ones at temperatures > 5 °C
- Wood/stone processing, packaging industry, feeding, handling, adjusting devices

Guarantee

igus chainflex

36

up to 36 months guarantee

igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year

UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

283

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Guarantee

igus chainflex

36

igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



Example image



Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
1 control pair shielded				
CF210.UL.15.15.02.01	(4G1.5+(2x1.5)C)	12.5	154	245
CF210.UL.25.15.02.01	(4G2.5+(2x1.5)C)C	14.0	210	299
CF210.UL.40.15.02.01	(4G4.0+(2x1.5)C)C	15.0	255	383
CF210.UL.60.15.02.01	(4G6.0+(2x1.5)C)C	16.5	343	488
2 control pairs shielded				
CF210.UL.15.07.02.02	(4G1.5+2x(2x0.75)C)C	13.5	161	278
CF210.UL.25.15.02.02	(4G2.5+2x(2x1.5)C)C	16.0	244	381
CF210.UL.40.15.02.02	(4G4.0+2x(2x1.5)C)C	17.0	332	428
CF210.UL.60.15.02.02	(4G6.0+2x(2x1.5)C)C	19.0	403	598
without control pair				
CF210.UL.05.04	(4G0.5)C	7.0	34	63
CF210.UL.15.04	(4G1.5)C	10.0	86	140
CF210.UL.25.04	(4G2.5)C	11.5	146	209
CF210.UL.40.04	(4G4.0)C	13.0	195	288

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Order example: **CF210.UL.40.15.02.01** - to your desired length (0.5m steps)
CF210.UL chainflex® series **.40** Code nominal cross section **.15** Code nominal cross section signal pairs
.02 Identification pairs **.01** Number of pairs

Order online ► www.igus.eu/CF210UL

Delivery time 24hrs or today.
Delivery time means time until goods are shipped.



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



chainflex® servo cable in a vertical e-chain®

Guarantee
igus chainflex
36

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year



Guarantee
igus chainflex
36
up to 36 months guarantee

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year



EPLAN download, configurators ► www.igus.eu/CF210UL

284 36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

EU2023



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

285