


Data sheet

chainflex® CFLG.LB



Fibre Optic Cable (Class 7.5.4.1) ● Graded index glass-fibre cable for heaviest duty applications ● TPE outer jacket ● Metal-free ● Oil and bio-oil resistant ● Low-temperature-flexible ● PVC and halogen-free ● UV-resistant



- 1. Outer jacket: Pressure extruded, halogen-free TPE mixture
- 2. Reinforcement: Extremely bending- and torsion-stable aramid braiding
- 3. Reinforcement: Extremely bending- and torsion-stable aramid wrapping
- 4. Filler: Aramid damper for high tensile stresses
- 5. Fibre tube: LSZH („Low smoke & zero halogen“) Material
- 6. Fibre: Glass optical fibre (GOF)

Example image
For detailed overview please see design table

Cable structure

	Fibre	62.5/125 µm, 50/125 µm, 9/125 µm especially bending-resistant solid glass fibre optic cores, with aramid strain relief elements.
	Core structure	FOC cores wound with a short pitch length with high-tensile aramid dampers.
	Core identification	Orange or blue or yellow with black numbers.
	Overall shield	Extremely bending-resistant aramid braid for torsion protection.
	Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®. Colour: Jet black (similar to RAL 9005) Printing: white

„00000 m*** igus chainflex CFLG.LB.---① ---② CE UKCA RoHS-II conform

www.igus.eu +++ chainflex cable works +++

* Length printing: Not calibrated. Only intended as an orientation aid.
① / ② Cable identification according to Part No. (see technical table).
Example: ... chainflex CFLG.2LB.50/125 2x50/125 ...



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



11/2023

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.

Data sheet

chainflex® CFLG.LB



Fibre Optic Cable (Class 7.5.4.1) ● Graded index glass-fibre cable for heaviest duty applications ● TPE outer jacket ● Metal-free ● Oil and bio-oil resistant ● Low-temperature-flexible ● PVC and halogen-free ● UV-resistant

Dynamic information

	Bend radius	e-chain® linear	min. 5 x d
		flexible	min. 4 x d
		fixed	min. 3 x d
	Temperature	e-chain® linear	-35 °C up to +80 °C
		flexible	-50 °C up to +80 °C (following DIN EN 60811-504)
		fixed	-55 °C up to +80 °C (following DIN EN 50305)
	v max.	unsupported	10 m/s
		gliding	6 m/s
	a max.	20 m/s ²	
	Travel distance	Unsupported travels and up to 100 m for gliding applications, Class 5 CFLG.12.LB: Unsupported travels and up to 400 m for gliding applications, Class 6	

These values are based on specific applications or tests. They do not represent the limit of what is technically feasible.

Guaranteed service life according to guarantee conditions

Double strokes	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-35/-25	7.5	8.5	9.5
-25/+70	5	6	7
+70/+80	7.5	8.5	9.5

Minimum guaranteed service life of the cable under the specified conditions.
The installation of the cable is recommended within the middle temperature range.



Example image

11/2023

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.

Data sheet

chainflex® CFLG.LB



Fibre Optic Cable (Class 7.5.4.1) ● Graded index glass-fibre cable for heaviest duty applications ● TPE outer jacket ● Metal-free ● Oil and bio-oil resistant ● Low-temperature-flexible ● PVC and halogen-free ● UV-resistant



Properties and approvals

	UV resistance	High
	Oil resistance	Oil-resistant (following DIN EN 60811-404), bio-oil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	Halogen-free	Following DIN EN 60754
	PFAS-free	Use of PFAS-free materials according to the content of the REACH directive and its rules for the production and processing of chemical substances
	UL verified	Certificate No. B129699: „igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF9.15.07 - tested by IPA according to standard DIN EN ISO 14644-1
	CE	Following 2014/35/EU



11/2023

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.

Data sheet


chainflex® CFLG.LB



Fibre Optic Cable (Class 7.5.4.1) ● Graded index glass-fibre cable for heaviest duty applications ● TPE outer jacket ● Metal-free ● Oil and bio-oil resistant ● Low-temperature-flexible ● PVC and halogen-free ● UV-resistant

Typical lab test setup for this cable series

Test bend radius R	approx. 38 - 75 mm
Test travel S	approx. 1 - 15 m
Test duration	minimum 2 - 4 million double strokes
Test speed	approx. 0.5 - 2 m / s
Test acceleration	approx. 0.5 - 1.5 m / s ²




Typical application areas

- For heaviest duty applications with 5-7.5 x d, Class 7
- Unsupported travel distances and up to 100 m for gliding applications (horizontal + vertical), Class 5
CFLG.12.LB: Unsupported travel distances and up to 400 m for gliding applications (horizontal + vertical), Class 6
- Almost unlimited resistance to oil, also with bio-oils, Class 4
- No torsion, Class 1
- Maximum EMC protection, with high transmission qualities
- Indoor and outdoor applications
- crane applications, Conveyor technique, Storage and retrieval units for high-bay warehouses, machining units/ packaging machines, quick handling, semiconductor insertion, refrigerating sector



Example image



11/2023

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.



Data sheet

chainflex® CFLG.LB



Fibre Optic Cable (Class 7.5.4.1) ● Graded index glass-fibre cable for heaviest duty applications ● TPE outer jacket ● Metal-free ● Oil and bio-oil resistant ● Low-temperature-flexible ● PVC and halogen-free ● UV-resistant

Technical tables:

Mechanical information

Part No.	Number of fibres/ Fibre diameter	Outer diameter (d) max. [mm]	Weight [kg/km]
Multimode (Graded index)			
CFLG.2LB.62.5/125	2x62.5/125	8.5	57
CFLG.4LB.62.5/125	4x62.5/125	9.0	68
CFLG.6LB.62.5/125	6x62.5/125	11.0	91
CFLG.12LB.62.5/125	12x62.5/125	14.0	150
CFLG.2LB.50/125	2x50/125	8.5	57
CFLG.4LB.50/125	4x50/125	9.0	68
CFLG.6LB.50/125	6x50/125	11.0	91
CFLG.12LB.50/125	12x50/125	14.0	150
Singlemode			
CFLG.12LB.9/125	12x9/125	15.0	125

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.

Optical features

Fibre diameter	Wave length	Bandwidth	Attenuation	Chromatic dispersion
[µm]	[nm]	[MHz x km]	[dB/km]	[ps/nm x km]
62.5/125	850	≥ 200	≤ 3.5	-
62.5/125	1300	≥ 500	≤ 1.5	-
50/125	850	≥ 500	≤ 3.5	-
50/125	1300	≥ 500	≤ 1.5	-
9/125	1310	-	≤ 0.5	3.5
9/125	1550	-	≤ 0.5	18



Example image



11/2023

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.

Design table

Fibre diameter: 62.5/125

Part No. (No. of cores)	Core design
CFLG.2LB.62.5/125 (2x62.5/125)	
CFLG.4LB.62.5/125 (4x62.5/125)	
CFLG.6LB.62.5/125 (6x62.5/125)	
CFLG.12LB.62.5/125 (12x62.5/125)	

Design table

Fibre diameter: 50/125

Part No. (No. of cores)	Core design
CFLG.2LB.50/125 (2x50/125)	
CFLG.4LB.50/125 (4x50/125)	
CFLG.6LB.50/125 (6x50/125)	
CFLG.12LB.50/125 (12x50/125)	

Design table

Fibre diameter: 9/125

Part No. (No. of cores)	Core design
CFLG.12LB.9/125 (12x9/125)	

© igus® GmbH. Subject to misprints and errors. Technical modifications are possible at any time. Maybe older batches do not have all or other features. Please refer regarding the availability of the items especially the information in the latest chainflex® catalogue.