

Fibre Optic Cable | PVC | chainflex® CFLG88

36 5,000,000 Double strokes guaranteed

7.5 x d Bend radius, e-chain®

10m Travel distance, e-chain®

- Graded index glass-fibre cable for flexing applications
- PVC outer jacket
- Flame-retardant

Dynamic information

	Bend radius	e-chain® linear	minimum 7.5 x d
		flexible	minimum 6 x d
		fixed	minimum 4 x d
	Temperature	e-chain® linear	+5°C up to +70°C
		flexible	-5°C up to +70°C (following DIN EN 60811-504)
		fixed	-15°C up to +70°C (following DIN EN 50305)
	v max.	unsupported	3m/s
	a max.		20m/s²
	Travel distance		Unsupported travels up to 10m, Class 1

Cable structure

	Fibre Optic Cable	50/125µm, 62.5/125µm bending-resistant solid glass fibre optic cores, with aramid strain relief elements.
	Core structure	FOC cores wound with a short pitch length with high-tensile aramid dampers.
	Core identification	FOC cores: Orange or blue with black numbers.
	Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®. Colour: jet black (similar to RAL 9005)

Properties and approvals

	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF240.02.24 - tested by IPA according to standard DIN EN ISO 14644-1
	CE	Following 2014/35/EU
	UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

EPLAN download, configurators ► www.igus.eu/CFLG88

36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

Class 3.1.1.1

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	7	≥ 400m
none	1	2	3	4	5	6	7	highest
none	1	2	3	4	5	6	7	±360°

Guaranteed service life (details see page 28-29)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	10	11	12
+15/+60	7.5	8.5	9.5
+60/+70	10	11	12

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For flexing applications, Class 3
- Especially for unsupported travels, Class 1
- Without influence of oil, Class 1
- No torsion, Class 1
- Highest EMC safety
- Preferably indoor applications
- Wood/stone processing, packaging industry, feeding, handling, adjusting devices

Part No.	Number of fibres/ Fibre diameter	Outer diameter (d) max. [mm]	Weight [kg/km]
CFLG88.2.62.5/125 ¹¹⁾	2x62.5/125	7.0	44
CFLG88.2.50/125	2x50/125	7.0	44

¹¹⁾ Phase-out model

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.

Part No.	Bandwidth [MHz x km] @ 850nm	Attenuation [dB/km] @ 850nm	Bandwidth [MHz x km] @ 1,300nm	Attenuation [dB/km] @ 1,300nm	Fibre identification
CFLG88.2.62.5/125	≥ 200	≤ 3.5	≥ 500	≤ 1.5	orange with black numbers
CFLG88.2.50/125	≥ 200	≤ 3.0	≥ 500	≤ 1.0	blue with black numbers



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case





igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year

223



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



Example image