

Measuring system cable | PUR | chainflex® CFROBOT4







36 10 million
Cycles guaranteed

10 x d
Bend radius, e-chain®







±180°/m
Torsion angle

- For torsion applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- Notch-resistant
- Hydrolysis and microbe-resistant



Dynamic information

	Bend radius	flexible twisted	minimum 10 x d
		fixed	minimum 5 x d
	Temperature	flexible twisted	-25°C up to +80°C
		fixed	-50°C up to +80°C (following DIN EN 50305)
	v max.	twisted	180°/s
	a max.	twisted	60°/s²
	Travel distance	Robots and 3D movements, Class 1	
	Torsion	Torsion ±180°, with 1m cable length, Class 3	

Cable structure

	Conductor	Stranded conductor in especially bending-resistant version consisting of tinned copper wires (following DIN EN 60228).	
	Core insulation	Mechanically high-quality TPE mixture.	
	Core identification	According to measuring system specification. ► Product range table	
	Element shield	Extremely torsion-resistant tinned wound copper shield.	
	Overall shield	Extremely torsion-resistant tinned wound copper shield. Coverage approx. 80% optical	
	Outer jacket	Low-adhesion, halogen-free, highly abrasion resistant PUR mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-10-2) Colour: Steel blue (similar to RAL 5011) Variants ► Product range table	

Electrical information

	Nominal voltage	50V 30V (following UL)
	Testing voltage	500V

EPLAN download, configurators ► www.igus.eu/CFROBOT4














36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

Class 6.1.3.3

Properties and approvals

	UV resistance	High
	Oil resistance	Oil-resistant (following DIN EN 50363-10-2), Class 3
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	Halogen-free	Following DIN EN 60754
	UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	See data sheet for details ► www.igus.eu/CFROBOT4
	NFPA	Following NFPA 79-2018, chapter 12.9
	EAC	Certificate No. RU C-DE.ME77.B.00295/19
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1 Following 2014/35/EU
	CE	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

Cycles*	5 million	7.5 million	10 million
Temperature, from/to [°C]	Torsion max. [°/m]	Torsion max. [°/m]	Torsion max. [°/m]
-25/-15	±150	±90	±30
-15/+70	±180	±120	±60
+70/+80	±150	±90	±30

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heaviest duty applications with torsion movements, Class 6
- Especially for robots and 3D movements, Class 1
- Almost unlimited resistance to oil, Class 3
- Torsion ±180°, with 1m cable length, Class 3
- Indoor and outdoor applications, UV-resistant
- Robots, handling, spindle drives

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



393

Example image

Measuring system cable | PUR | chainflex® CFROBOT4

Class 6.1.3.3

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			



Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFROBOT4.001	(3x(2x0.14)C + (4x0.14)+(2x0.5))C	10.5	62	115
CFROBOT4.006	(3x(2x0.14C+(4x0.14) + (4x0.22)+(2x0.5))C	11.5	74	135
CFROBOT4.009	(4x(2x0.25)+(2x0.5))C	9.0	48	90
CFROBOT4.015	(4x(2x0.14)+4x0.5)C	9.0	49	91
CFROBOT4.028 ¹³⁾	(2x(2x0.20)+(2x0.38))C	7.5	44	72

¹³⁾ Colour outer jacket: Yellow-green (RAL 6018)

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

Part No.	Core group	Colour code
CFROBOT4.001	3x(2x0.14)C	green/yellow, black/brown, red/orange
	4x0.14	grey/blue/white-yellow/white-black
	2x0.5	brown-red/brown-blue
CFROBOT4.006	3x(2x0.14)C	green/yellow, black/brown, red/orange
	(4x0.14)	grey/blue/white-yellow/white-black
	(4x0.22)	yellow-brown/grey-brown/green-black/green-red
	(2x0.5)	brown-red/brown-blue
CFROBOT4.009	4x(2x0.25)	brown/green, blue/violet, grey/pink, red/black
	2x0.5	white, brown
CFROBOT4.015	4x(2x0.14)	brown/green, yellow/violet, grey/pink, red/black
	4x0.5	blue, white, brown-green, white-green
CFROBOT4.028 ¹³⁾	2x(2x0.20)	green/yellow, pink/blue
	(2x0.38)	red/black



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



Order example: **CFROBOT4.009** – to your desired length (0.5m steps)
CFROBOT4 chainflex® series **.009** Code measuring system type



Order online ► www.igus.eu/CFROBOT4



Delivery time 24hrs or today.
Delivery time means time until goods are shipped.

EPLAN download, configurators ► www.igus.eu/CFROBOT4

394 36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

EU2023



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

395

