

Control cable | PVC | chainflex® CFSOFT1

36

20 million

Double strokes guaranteed

5 x d

Bend radius, e-chain®

5m

Travel distance, e-chain®

- For heaviest duty applications and very small radii down to 5 x d
 - Highly flexible, soft design
 - PVC outer jacket
- Oil-resistant
 - Flame-retardant

Dynamic information

	Bend radius	e-chain® linear	minimum 5 x d
		flexible	minimum 4 x d
		fixed	minimum 3 x d
	Temperature	e-chain® linear	+5°C up to +70°C
		flexible	-5°C up to +70°C (following DIN EN 60811-504)
		fixed	-15°C up to +70°C (following DIN EN 50305)
	v max.	unsupported	10m/s
	a max.	gliding	5m/s
	Travel distance	Short, very fast applications with small radii and restricted installation space, Class 1	

Cable structure

	Conductor	Very finely stranded special conductors with especially soft and bending resistant design, made of bare copper wires.
	Core insulation	Mechanically high-quality TPE mixture.
	Core structure	Cores wound in a layer with especially short pitch length.
	Core identification	Colour code in accordance with DIN 47100.
	Outer jacket	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-4-1). Colour: jet black (similar to RAL 9005)

Electrical information

	Nominal voltage	300/500V (following DIN VDE 0298-3) 300V (following UL)
	Testing voltage	2,000V (following DIN EN 50395)

Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (following DIN EN 50363-4-1), Class 2
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)

EPLAN download, configurators ► www.igus.eu/CFSOFT1

36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges



EU2023

Class 7.1.2.1

UL verified

UL/CSA AWM

NFPA

EAC

REACH

Lead-free

Cleanroom

CE

UKCA

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
See data sheet for details ► www.igus.eu/CFSOFT1

Following NFPA 79-2018, chapter 12.9

Certificate No. RU C-DE.ME77.B.00300/19

In accordance with regulation (EC) No. 1907/2006 (REACH)

Following 2011/65/EC (RoHS-II/RoHS-III)

According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1
Following 2014/35/EU

In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Guaranteed service life (details see page 28-29)

Double strokes*	10 million	15 million	20 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	6.8	7.5	8.5
+15/+60	5	6	7
+60/+70	6.8	7.5	8.5

* Higher number of double strokes? Service life calculation online ► www.igus.eu/chainflexlife

Typical application areas

- For heaviest duty applications and very small radii down to 5 x d, Class 7
- Especially for short, very fast applications with small radii and restricted installation space, Class 1
- Light oil influence, Class 2
- No torsion, Class 1
- Especially soft cable design, for reduced forces
- Pick and place machines, automatic doors, cleanroom, very quick handling

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFSOFT1.02.03	3x0.25	5.5	9	28
CFSOFT1.02.08	8x0.25	7.0	21	62
CFSOFT1.03.04	4x0.34	6.0	15	39
CFSOFT1.05.04	4x0.5	7.0	21	52

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case

