


Hybrid cable for top drive applications | PUR  
chainflex® CFSPECIAL.592






- For top drive applications
- For heavy duty applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- UV-resistant
- Hydrolysis and microbe-resistant

Now with DNV  
approval for  
top drive hanging  
applications  
up to 50m

Dynamic information

	<b>Bend radius</b>	<b>e-chain® linear</b>	minimum 10 x d
		<b>flexible</b>	minimum 8 x d
		<b>fixed</b>	minimum 5 x d
	<b>Temperature</b>	<b>e-chain® linear</b>	-25°C up to +80°C
		<b>flexible</b>	-40°C up to +80°C (following DIN EN 60811-504)
		<b>fixed</b>	-50°C up to +80°C (following DIN EN 50305)
	<b>v max.</b>	<b>unsupported</b>	10m/s
	<b>a max.</b>	<b>sliding</b>	2m/s
	<b>Travel distance</b>	For top drive hanging applications up to 50m	











Cable structure

	<b>Conductor</b>	Stranded conductor in especially bending-resistant version consisting of bare copper wires (following DIN EN 60228).
	<b>Core insulation</b>	Mechanically high-quality, especially low-capacitance XLPE mixture.
	<b>Inner jacket</b>	Mechanically high-quality TPE mixture.
	<b>Overall shield</b>	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	<b>Outer jacket</b>	<b>1. Outer jacket:</b> PUR mixture adapted to suit the requirements in e-chains®. <b>Reinforcement:</b> High tensile strength aramid braid embedded in the outer jacket. <b>2. Outer jacket:</b> Low-adhesion, halogen-free PUR mixture, highly abrasion and bending-resistant, adapted to suit the requirements in top drive hanging applications (following DIN EN 50363-10-2). Colour: jet black (similar to RAL 9005)

Electrical information

	<b>Nominal voltage</b>	600/1,000V (following DIN VDE 0298-3) 1,000V (following UL)
	<b>Testing voltage</b>	4,000V (following DIN EN 50395)

Properties and approvals

	<b>UV resistance</b>	High
	<b>Oil resistance</b>	Oil-resistant (in accordance with DIN EN 50363-10-2)
	<b>Offshore</b>	MUD-resistant following NEK 606 - status 2016
	<b>Flame-retardant</b>	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	<b>Silicone-free</b>	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	<b>Halogen-free</b>	Following DIN EN 60754
	<b>UL verified</b>	Certificate No. B129699: „igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	<b>UL/CSA AWM</b>	See data sheet for details ► <a href="http://www.igus.eu/CFSPECIAL592">www.igus.eu/CFSPECIAL592</a>
	<b>NFPA</b>	Following NFPA 79-2018, chapter 12.9
	<b>DNV</b>	Type Approval Certificate TAE00004KR
	<b>REACH</b>	In accordance with regulation (EC) No. 1907/2006 (REACH)
	<b>Lead-free</b>	Following 2011/65/EC (RoHS-II)
	<b>CE</b>	Following 2014/35/EU
	<b>UKCA</b>	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Typical application areas

- For high tensile loads
- Almost unlimited resistance to oil
- For top drive hanging applications up to 50m

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
<b>CFSPECIAL.592.001</b>	(30G4.0+4x(2x2.5)C)C	44.0	1,750	2630

**Note:** The given outer diameters are maximum values and may tend toward lower tolerance limits.  
G = with green-yellow earth core   x = without earth core



EPLAN download, configurators ► [www.igus.eu/CFSPECIAL592](http://www.igus.eu/CFSPECIAL592)



EU2023

EU2023



36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges 439