

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on stockpiles

OPERATION QUALITIES

- Inlet diameter DN300
- max. flow rate 250 m³/h
- particle size 0-50 mm
- pipe for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drives 1.6 - 2.2 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 2x rotary
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- design for ATEX / non-standard temperature (-40 °C / +250 °C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
2360	8 000	5 640	776
2500	10 000	7 500	900
2780	11 986	9 206	930
2890	14 000	11 110	1013
3800	15 000	11 200	1310



0 - 50



max. 250 m³/h

Telescopic loading spout type NZO300S with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on stockpiles and ships.

3.1. STANDARD LINE

3.1.1. NZO300S

