

DESCRIPTION

- telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. loading rate 300 m³/h
- particle size 0 - 80 mm
- inlet diameter DN 400
- operating temperature -20 °C / +80 °C
- motor drive 0.55 - 0.75 kW
- loading conduit consisting of internal cones and external bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – rotary / vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- pendant or remote control
- vibration unit
- design for ATEX
- non-standard temperature (-40 °C / +250 °C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
1460	3500	2040	255
1510	4200	2690	269
1560	4600	3040	283
1610	5000	3390	297
1660	5400	3740	310
1710	5800	4090	324
1760	6200	4440	338



0 - 80



max. 300 m³/h

Telescopic loading spout type NZO400E with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

