

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- inlet diameter DN400
- max. flow rate 400 m³/h
- particle size 0-100 mm
- pipe for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drive 1.25 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – rotary / vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- pendant or remote control
- vibration unit
- shut off valves (manual, electro, pneumatic)
- design for ATEX / non-standard temperature (-40 °C / +250 °C)

L_{min} (retracted lenght)	L_{max} (extracted lenght)	Travel (H)	Weight
1 250	3 500	2 250	489
1 400	3 900	2 500	531
1 700	4 500	3 000	484
1 800	5 750	3 950	633
1 800	6 400	4 600	669



0 - 100



max. 400 m³/h

Robust-design telescopic loading spout type NZO400S with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

