

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. loading rate 450-500 m³/h
- particle size 0-80 mm
- inlet diameter DN 500
- operating temperature -20 °C / +80 °C
- motor drive 1.25 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – rotary / vibrating
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- pendant or remote control
- vibration unit
- design for ATEX
- non-standard temperature (-40 °C/+250 °C)

L_{min} (retracted length)	L_{max} (extracted length)	Travel (H)	Weight
1400	3500	2100	565
1460	4000	2540	590
1600	4500	2900	620
1635	5160	3525	666
1775	5750	3975	692
1830	6200	4370	730



0 - 80



max. 500 m³/h

Telescopic loading spout type NZO500S with the dustproof bell, rubber skirt and level indicator guarantee you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

