

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. flow rate 500 m³/h
- particle size 0-100 mm
- inlet diameter DN600
- pipe for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drive 2.2 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 2x rotary
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- shut off valves (manual, electro, pneumatic)
- design for ATEX / non-standard temperature (-40 °C / +250 °C)

| L _{min} (retracted length) | L _{max} (extracted length) | Travel (H) | Weight |
|--|--|------------|--------|
| 1940 | 3635 | 1695 | 631 |
| 1900 | 4670 | 2770 | 949 |
| 2160 | 4729 | 2569 | 704 |
| 2160 | 5060 | 2900 | 798 |
| 2230 | 5151 | 2921 | 750 |
| 2490 | 6150 | 3660 | 823 |
| 2600 | 6700 | 4100 | 906 |
| 2650 | 7200 | 4550 | 1100 |
| 2700 | 7700 | 5000 | 1125 |
| 2800 | 8200 | 5400 | 1170 |



0 - 100



max. 500 m³/h



Robust-design telescopic loading spout type NZO600H with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

2.3. HEAVY LINE

2.3.1. NZO600H

