

Clevis joints with clevis pin and circlip:
GERMK and GELMK



- Lightweight
- Absolute corrosion resistance
- High tensile force
- Can be combined with E series rod end

Order key

Type	Size [mm]	Options
GE□MK-04		LS
Clevis joint	E series	Thread
	Metric	Clevis pin and circlip
	Inner Ø	

Thread
L = Left-hand thread
R = Right-hand thread

Add-on:
LS = Longer shank

Material:
igumid G ► Page 1654

Service life calculation online
► www.igus.eu/igus-expert

Technical data

Part No.	Max. static tensile strain		Max. static axial force		Weight [g]
	Short-term [N]	Long-term [N]	Short-term [N]	Long-term [N]	
GE□MK-04 M3.5	500	250	250	125	1.3
GE□MK-04	500	250	250	125	1.3
GE□MK-05 DIN M4	800	400	250	125	2.1
GE□MK-05 DIN M5	800	400	250	125	2.1
GE□MK-05	900	450	250	125	3.3
GE□MK-05 DIN M5 LS ²²⁾	800	400	130	65	2.9
GE□MK-06	1,300	650	300	150	3.3
GE□MK-06 LS ²²⁾	1,300	650	130	65	4.4
GE□MK-08	2,100	1,050	650	325	7.9
GE□MK-10	3,000	1,500	800	400	16.4
GE□MK-10 F	3,000	1,500	800	400	16.4
GE□MK-12	3,500	1,750	900	450	25.3
GE□MK-12 F	3,500	1,750	900	450	25.3
GE□MK-14	6,100	3,050	1,000	500	31.2
GE□MK-15	2,800	1,400	1,000	500	38.9
GE□MK-16	7,000	3,500	1,200	600	60.8
GE□MK-16 F	7,000	3,500	1,200	600	60.8
GE□MK-17	3,600	1,800	1,200	600	62.3
GE□MK-17 F	3,600	1,800	1,200	600	62.3
GE□MK-20	9,000	4,500	3,000	1,500	125.2
GE□MK-20 M20	9,000	4,500	3,000	1,500	125.2

²²⁾ LS = longer shank



Single components: clevis pin
GBM and circlip GSR
► Page 783

778 Online tools and more information ► www.igus.eu/clevis



Clevis joints with spring-loaded fixing clip:
GERMF and GELMF



- One-piece design
- Easy assembly/disassembly
- Easy assembly also for use in hard to reach locations
- Can be combined with E series rod end
- Corrosion-resistant and lightweight

Order key

Type	Size [mm]	Options
GE□MF-04		LS
Clevis joint	E series	Thread
	Metric	Spring-loaded fixing clip
	Inner Ø	

Thread
L = Left-hand thread
R = Right-hand thread

Add-on:
LS = Longer shank

Material:
igumid G ► Page 1654

Service life calculation online
► www.igus.eu/igus-expert

Technical data

Part No.	Max. static tensile strain		Max. static axial force		Weight [g]
	Short-term [N]	Long-term [N]	Short-term [N]	Long-term [N]	
GE□MF-04 M3.5	500	250	250	125	1.3
GE□MF-04	500	250	250	125	1.3
GE□MF-05 DIN M4	800	400	250	125	2.3
GE□MF-05 DIN M5	800	400	250	125	2.3
GE□MF-05 DIN M5 LS ²²⁾	800	400	130	65	2.3
GE□MF-05	900	450	250	125	3.8
GE□MF-06	1,300	650	300	150	3.9
GE□MF-06 LS ²²⁾	1,300	650	130	65	3.9
GE□MF-08	2,100	1,050	650	325	9.1
GE□MF-10	3,000	1,500	800	400	18.2
GE□MF-10 F	3,000	1,500	800	400	18.2
GE□MF-12	3,500	1,750	900	450	28.6
GE□MF-12 F	3,500	1,750	900	450	28.6
GE□MF-16	7,000	3,500	1,200	600	61.8
GE□MF-16 F	7,000	3,500	1,200	600	61.8

²²⁾ LS = longer shank



Single components: Spring-loaded fixing clip GEFM
► Page 782



3D CAD files, prices and delivery time online ► www.igus.eu/clevis 779