






Accessories

Ball joints / Nipple

Ball joints

For swivel mounting, Lechler ball joints can be used with low-noise flat jet and round jet nozzles. 30° swivel range in all directions. No wearing seals, long-term problemfree operation, even with frequent adjustment.

$p_{max} = 25 \text{ bar}$




Connection	Ordering no.					Dimensions [mm]											Weight (Brass)
	Type	Mat. no.			Code												
		16 303 SS/ 316Ti SS	16 303 SS	30 Brass													
						D ₁	D ₂	G ₁ BSPP	G ₂ BSPP	L _{G1}	L _{G2}	L	Hex ₁	Hex ₂	Hex ₃		
Ball joints with thread connection	① 092.020	-	○	○	AD	-	-	1/4	1/4	12.0	11.5	60.3	27	27	17	60 g	
	① 092.021	-	○	○	AF	-	-	3/8	1/4	12.0	11.5	58.3	27	27	17	80 g	
	② 092.024	-	○	○	AC	-	-	1/4	1/4	12.0	12.0	44.0	27	27	-	140 g	
	② 092.030	-	○	○	AE	-	-	3/8	3/8	12.0	12.0	44.0	27	30	-	160 g	
Ball joints with welding connection	③ 092.020	○	-	-	SD	20.0	15.0	-	1/4	-	11.5	64.3	-	27	17	60 g	
	③ 092.030	○	-	-	SF	22.0	15.0	-	3/8	-	12.0	58.7	-	30	19	80 g	

Example	Type	+	Mat. no.	+	Code	=	Ordering no.
of ordering:	092.020	+	16	+	AD	=	092.020.16.AD

Nipple

095.016.30.14.23.0
The nipple made of brass allows for connection of nozzles with compressed air guns. Suitable for the series:
■ 600.130
■ 600.283
■ 600.332
■ 600.606
■ 600.493
■ 600.484
■ 600.326
■ 544







Accessories

Eyelet clamps / Double nipples / Nuts


Eyelet clamps



Ordering no.				Screw	Dimensions [mm]									Weght (Polyamid)
Type	Mat. no.													
	51 Polyamid	53 Polypropylene	5E PVDF											
					Pipe Ø	D Ø	B _R * Ø	B** Ø	B ₁	B ₂	B ₃	H ₁	H ₂	
090.053	○	○	○	Material 304 SS	3.8"	16.5-18.0	6.0	6.2 - 6.4	19.0	22.0	18.5	34.5	14.5	20 g
090.003	○	○	○		1/2"	20 - 22.0	6.0	6.2 - 6.4	21.2	23.8	18.5	36.5	16.5	20 g
090.013	○	○	○		3/4"	25 - 27.5	7.6	7.8 - 8.0	24.5	26.5	22.0	39.5	17.5	25 g
090.023	○	○	○		1"	32 - 34.5	10.6	10.8 - 11.0	30.0	31.0	22.0	44.0	21.0	32 g
090.033	○	○	○		1 1/4"	40 - 43.0	12.6	12.8 - 13.0	34.0	35.5	25.0	48.0	25.0	38 g
090.012	-	-	○	316 SS	3/4"	25 - 27.5	7.8	8.0 - 8.2	19.5	21.0	22.0	31.5	18.0	40 g


*B_R Ø = Spigot diameter
**B Ø = Recommended bore diameter

Double nipples



Ordering no.		Mat. no.			Dimensions [mm]								Weight (Brass)
Type		17	30		G ₁ BSPP	G ₂ BSPP	H ₁	H ₂	D ₁	D ₂	Hex		
065.215		○	○		3/8	1/4	25	10	10	7	22		30 g
065.211		○	○		3/8	3/8	25	10	11.5	-	22		25 g

Retaining nuts



Ordering no.		Mat. no.					Dimensions [mm]					Weight (Brass)
Type		16	17	30	56	5E	G BSPP	H ₁	H ₂	D	Hex	
065.200		○	○	○	-	-	3/8	13.0	10.0	12.8	22	25 g
065.200		-	-	-	○	○	3/8	14.5	11.5	12.8	22	25 g