

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on stockpiles

OPERATION QUALITIES

- inlet diameter DN600
- max. flow rate approx. 1000 m³/h
- particle size 0-100 mm
- pipe for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drives 3 - 5,5 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 2x rotary
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- design for ATEX / non-standard temperature (-40°C/+250°C)

L _{min} (retracted length)	L _{max} (extracted length)	Travel (H)	Weight
2830	9 250	6 420	2108
3050	13 250	10 200	2300
3500	15 000	11 500	2755
3500	16 539	13 093	2761
3750	18 300	14 550	3315
4700	20 100	15 400	3360



Robust-design telescopic loading spout type NZO600DH with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on stockpiles or ships.