

Network

Network / Ethernet / Fieldbus



chainflex® readycable®





	Series	Jacket	Page
Harnessed Ethernet cables			
	CAT5 Straight	PVC/PUR/TPE	471
	SPE Single Pair Ethernet	PUR	471 New
	CAT5e Straight	PVC/PUR/TPE	472
	CAT5e Straight	PVC/PUR/TPE	475
	CAT5e Crossover	PVC/PUR/TPE	476
	CAT5e with 615 connectors	PVC/PUR/TPE	477
	CAT5e with angled connectors (L/T angle)	PVC/PUR/TPE	478
	CAT6 Straight	PVC/PUR/TPE	482
	CAT6 Straight/Crossover	TPE	484
	CAT6A with M12 connectors	PVC/PUR/TPE	485
	CAT7 Straight	PUR/TPE	487
	Industrial Ethernet moulded	PVC/PUR	488
Harnessed Profibus cables			
	Profibus	PVC/PUR/TPE	490
Harnessed Profinet cables			
	Profinet	PVC/PUR/TPE	496 New
	Industrial Profinet moulded	PVC/PUR	502



UL-verified chainflex® guarantee ... www.igus.eu/ul-verified

469



Highly flexible chainflex® cables

- More than 1,350 cables from stock
- Tested, and in seven jacket materials
- No cutting charges, from 1m
- 36-month or 10 million double stroke guarantee*
- Approvals and certificates

Harnessed cables readycable®

- More than 400 harnessed Ethernet cables
- In seven jacket materials
- 36-month or 10 million double stroke guarantee*
- Shipped in 24hrs**
- To your desired length, with centimetre accuracy

harnessed e-chain® systems readychain®

- Customised and ready-to-connect to your specifications
- From the basic solution to complex systems
- Optional assembly rack
- From batch size 1 to series production
- Installation service

* Whichever is first. Up to 5 million double strokes for the highly affordable chainflex® M cables. The number of double strokes depends on installation and cable quality. This is described in the current catalogue, in the data sheets and in the service life calculator at www.igus.eu/chainflexlife.

** Means time until shipping of goods.

* Technical information on the cable quality:

PVC, oil-res.	PUR	TPE
Page 184	Page 192	Page 196

Harnessed Ethernet cables, CAT5, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Harting RJ45 (CAT5)/ Harting RJ45 (CAT5)				
PVC, oil-res.	CAT9311001	(4x0.25)C	6.5	12.5
PUR	CAT9411001	(4x0.25)C	6.5	12.5
TPE	CAT9511001	(4x0.25)C	7.0	10
Harting Han3A RJ45 (CAT6)/ Harting Han3A RJ45 (CAT6)				
PVC, oil-res.	CAT9311002	(4x0.25)C	6.5	12.5
PUR	CAT9411002	(4x0.25)C	6.5	12.5
TPE	CAT9511002	(4x0.25)C	7.0	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ► TIA56A
Harnessing one end RJ45/one end M12 x-coded ► TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

* Technical information on the cable quality:

PUR
Page 192

Harnessed Single Pair Ethernet (SPE) cable, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Harting T1 Single Pair Ethernet Connector/ Harting T1 Single Pair Ethernet Connector				
PUR	CAT9471001 New	(2x0.15)C	5.5	12.5



Single Pair Ethernet is the infrastructure foundation that makes IIoT and Industry 4.0 possible. In order to promote Single Pair Ethernet technology for the rapidly growing IIoT market, igus is participating in the SPE Industrial Partner Networks with other established partners such as HARTING and TE Connectivity.

More information: www.igus.eu/info/n20-single-pair-ethernet-spe

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	PUR-SPECIAL	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 416	Page 196

Harnessed Ethernet cables, CAT5e, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]

Telegärtner RJ45 (CAT6A)/
Telegärtner RJ45 (CAT6A)



PVC	CAT9121002	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321002	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221002	(4x(2x0.14))C	7.0	15
PUR	CAT9421002	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621002	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721001	(4x(2x0.15))C	9.5	10
TPE	CAT9521002	(4x(2x0.15))C	8.5	10

Harting RJ45 (CAT6A)/
Harting RJ45 (CAT6A)



PVC	CAT9121003	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321003	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221003	(4x(2x0.14))C	7.0	15
PUR	CAT9421003	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621003	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721002	(4x(2x0.15))C	9.5	10
TPE	CAT9521003	(4x(2x0.15))C	8.5	10

Telegärtner RJ45 (CAT6)/
Telegärtner RJ45 (CAT6)



PVC	CAT9121004	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321004	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221004	(4x(2x0.14))C	7.0	15
PUR	CAT9421004	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621004	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721003	(4x(2x0.15))C	9.5	10
TPE	CAT9521004	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	PUR-SPECIAL	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 416	Page 196

Harnessed Ethernet cables, CAT5e, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]

Telegärtner RJ45 (CAT6)/
Telegärtner RJ45 angled (CAT6A)



PVC	CAT9121005	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321005	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221005	(4x(2x0.14))C	7.0	15
PUR	CAT9421005	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621005	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721004	(4x(2x0.15))C	9.5	10
TPE	CAT9521005	(4x(2x0.15))C	8.5	10

Telegärtner RJ45 (CAT6)/
Telegärtner M12 x-coded (CAT6)



PVC	CAT9121006	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321006	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221006	(4x(2x0.14))C	7.0	15
PUR	CAT9421006	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621006	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721005	(4x(2x0.15))C	9.5	10
TPE	CAT9521006	(4x(2x0.15))C	8.5	10

Telegärtner M12 x-coded (CAT6A)/
Telegärtner M12 x-coded (CAT6A)



PVC	CAT9121007	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321007	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221007	(4x(2x0.14))C	7.0	15
PUR	CAT9421007	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621007	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721006	(4x(2x0.15))C	9.5	10
TPE	CAT9521007	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	PUR-SPECIAL	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 416	Page 196

Harnessed Ethernet cables, CAT5e, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Phoenix Contact RJ45 (CAT6A)/ Phoenix Contact RJ45 (CAT6A)				
PVC	CAT9121010	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321010	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221010	(4x(2x0.14))C	7.0	15
PUR	CAT9421010	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621010	4x(2x0.15)C	9.5	10
TPE	CAT9521010	(4x(2x0.15))C	8.5	10
Phoenix Contact M12 x-coded (CAT6A)/ Phoenix Contact M12 x-coded (CAT6A)				
PVC	CAT9121013	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321013	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221013	(4x(2x0.14))C	7.0	15
PUR	CAT9421013	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621013	4x(2x0.15)C	9.5	10
PUR-SPECIAL	CAT9721011	(4x(2x0.15))C	9.5	10
TPE	CAT9521013	(4x(2x0.15))C	8.5	10
Harting M12 x-coded Socket (CAT6A)/ Harting M12 x-coded Pin (CAT6A)				
PVC	CAT9121014	(4x(2x0.14))C	7.0	15
PVC, oil-res.	CAT9321014	(4x(2x0.15))C	7.5	12.5
iguPUR	CAT9221014	(4x(2x0.14))C	7.0	15
PUR	CAT9421014	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9621014	4x(2x0.15)C	9.5	10
TPE	CAT9521014	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC, oil-res.	PUR	PUR-ROBOT	TPE
Page 184	Page 192	Page 398	Page 196

Harnessed Ethernet cables, CAT5e Straight, 4 and 8-pole, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Harting RJ45 (CAT5)/ Harting RJ45 (CAT5)				
TPE	CAT9040001	(4x0.25)C	7.0	10
Harting RJ45 (CAT5e)/ Harting RJ45 (CAT5e)				
PVC, oil-res.	CAT9340020	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240020	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440020	4x(2x0.15)C	9.5	10
TPE	CAT9040020	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5)/ Yamaichi RJ45 (CAT5)				
PVC, oil-res.	CAT9340060	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240060	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440060	4x(2x0.15)C	9.5	10
TPE	CAT9040060	(4x(2x0.15))C	8.5	10
Phoenix Contact RJ45 (CAT5e)/ Phoenix Contact RJ45 (CAT5e)				
PVC, oil-res.	CAT9340100	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240100	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440100	4x(2x0.15)C	9.5	10
TPE	CAT9040100	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5) in Hummel M23 housing/ Yamaichi RJ45 (CAT5) in Hummel M23 housing				
PVC, oil-res.	CAT9340140	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240140	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440140	4x(2x0.15)C	9.5	10
TPE	CAT9040140	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5) in Hummel M23 housing/ Yamaichi RJ45 (CAT5) in Hummel M23 coupling housing				
PVC, oil-res.	CAT9340180	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240180	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440180	4x(2x0.15)C	9.5	10
TPE	CAT9040180	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC, oil-res.	PUR	PUR-ROBOT	TPE
Page 184	Page 192	Page 398	Page 196

Harnessed Ethernet cables, CAT5e Crossover, 8-pole, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Harting RJ45 (CAT5e)/ Harting RJ45 (CAT5e) 				
PVC, oil-res.	CAT9340040	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240040	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440040	4x(2x0.15)C	9.5	10
TPE	CAT9040040	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5)/ Yamaichi RJ45 (CAT5) 				
PVC, oil-res.	CAT9340080	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240080	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440080	4x(2x0.15)C	9.5	10
TPE	CAT9040080	(4x(2x0.15))C	8.5	10
Phoenix Contact RJ45 (CAT5e)/ Phoenix Contact RJ45 (CAT5e) 				
PVC, oil-res.	CAT9340120	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240120	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440120	4x(2x0.15)C	9.5	10
TPE	CAT9040120	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5) in Hummel M23 housing/Yamaichi RJ45 (CAT5) in Hummel M23 housing 				
PVC, oil-res.	CAT9340160	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240160	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440160	4x(2x0.15)C	9.5	10
TPE	CAT9040160	(4x(2x0.15))C	8.5	10
Yamaichi RJ45 (CAT5) in Hummel M23 housing/Yamaichi RJ45 (CAT5) in Hummel M23 coupling housing 				
PVC, oil-res.	CAT9340200	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440200	4x(2x0.15)C	9.5	10
TPE	CAT9040200	(4x(2x0.15))C	8.5	10
PUR	CAT9240200	(4x(2x0.15))C	7.5	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT5e

* Technical information on the cable quality:

PVC, oil-res.	PUR	PUR-ROBOT	TPE
Page 184	Page 192	Page 398	Page 196

Harnessed Ethernet cables, CAT5e, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Hirose RJ45 (CAT5e)/ TE Intercontec 615 signal connector 				
PVC, oil-res.	CAT9340800	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240800	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440800	4x(2x0.15)C	9.5	10
TPE	CAT9040800	(4x(2x0.15))C	8.5	10
TE Intercontec 615 signal coupling/ TE Intercontec 615 signal connector 				
PVC, oil-res.	CAT9340810	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240810	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440810	4x(2x0.15)C	9.5	10
TPE	CAT9040810	(4x(2x0.15))C	8.5	10
TE Intercontec 615 signal coupling/ Hirose RJ45 (CAT5e) 				
PVC, oil-res.	CAT9340820	(4x(2x0.15))C	7.5	12.5
PUR	CAT9240820	(4x(2x0.15))C	7.5	12.5
PUR-ROBOT	CAT9440820	4x(2x0.15)C	9.5	10
TPE	CAT9040820	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT5e
PVC oil-res. with Hirose connectors

* Technical information on the cable quality:
PVC, oil-res.
Page 184

Harnessed Ethernet cables, CAT5e, PVC, with Hirose connectors, 8-pole, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Straight				
1 2	CAT9340380	(4x(2x0.15))C	7.5	12.5
1 3	CAT9340540	(4x(2x0.15))C	7.5	12.5
1 4	CAT9340560	(4x(2x0.15))C	7.5	12.5
1 5	CAT9340320	(4x(2x0.15))C	7.5	12.5
2 1	CAT9340360	(4x(2x0.15))C	7.5	12.5
2 2	CAT9340340	(4x(2x0.15))C	7.5	12.5
2 3	CAT9340500	(4x(2x0.15))C	7.5	12.5
2 4	CAT9340520	(4x(2x0.15))C	7.5	12.5
2 5	CAT9340300	(4x(2x0.15))C	7.5	12.5
3 3	CAT9340440	(4x(2x0.15))C	7.5	12.5
3 4	CAT9340480	(4x(2x0.15))C	7.5	12.5
3 5	CAT9340400	(4x(2x0.15))C	7.5	12.5
4 4	CAT9340460	(4x(2x0.15))C	7.5	12.5
4 5	CAT9340420	(4x(2x0.15))C	7.5	12.5
Crossover				
1 2	CAT9340390	(4x(2x0.15))C	7.5	12.5
1 3	CAT9340550	(4x(2x0.15))C	7.5	12.5
1 4	CAT9340570	(4x(2x0.15))C	7.5	12.5
1 5	CAT9340330	(4x(2x0.15))C	7.5	12.5
2 1	CAT9340370	(4x(2x0.15))C	7.5	12.5
2 2	CAT9340350	(4x(2x0.15))C	7.5	12.5
2 3	CAT9340510	(4x(2x0.15))C	7.5	12.5
2 4	CAT9340530	(4x(2x0.15))C	7.5	12.5
2 5	CAT9340310	(4x(2x0.15))C	7.5	12.5
3 3	CAT9340450	(4x(2x0.15))C	7.5	12.5
3 4	CAT9340490	(4x(2x0.15))C	7.5	12.5
3 5	CAT9340410	(4x(2x0.15))C	7.5	12.5
4 4	CAT9340470	(4x(2x0.15))C	7.5	12.5
4 5	CAT9340430	(4x(2x0.15))C	7.5	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed with these connectors				
Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
L angle curve lower	L angle curve upper	T angle curve outer	T angle curve inner	straight
				

Harnessed Ethernet cables | CAT5e
PUR with Hirose connector

* Technical information on the cable quality:
PUR
Page 192

Harnessed Ethernet cables, CAT5e, PUR, with Hirose connectors, 8-pole, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Straight				
1 2	CAT9240380	(4x(2x0.15))C	7.5	12.5
1 3	CAT9240540	(4x(2x0.15))C	7.5	12.5
1 4	CAT9240560	(4x(2x0.15))C	7.5	12.5
1 5	CAT9240320	(4x(2x0.15))C	7.5	12.5
2 1	CAT9240360	(4x(2x0.15))C	7.5	12.5
2 2	CAT9240340	(4x(2x0.15))C	7.5	12.5
2 3	CAT9240500	(4x(2x0.15))C	7.5	12.5
2 4	CAT9240520	(4x(2x0.15))C	7.5	12.5
2 5	CAT9240300	(4x(2x0.15))C	7.5	12.5
3 3	CAT9240440	(4x(2x0.15))C	7.5	12.5
3 4	CAT9240480	(4x(2x0.15))C	7.5	12.5
3 5	CAT9240400	(4x(2x0.15))C	7.5	12.5
4 4	CAT9240460	(4x(2x0.15))C	7.5	12.5
4 5	CAT9240420	(4x(2x0.15))C	7.5	12.5
Crossover				
1 2	CAT9240390	(4x(2x0.15))C	7.5	12.5
1 3	CAT9240550	(4x(2x0.15))C	7.5	12.5
1 4	CAT9240570	(4x(2x0.15))C	7.5	12.5
1 5	CAT9240330	(4x(2x0.15))C	7.5	12.5
2 1	CAT9240370	(4x(2x0.15))C	7.5	12.5
2 2	CAT9240350	(4x(2x0.15))C	7.5	12.5
2 3	CAT9240510	(4x(2x0.15))C	7.5	12.5
2 4	CAT9240530	(4x(2x0.15))C	7.5	12.5
2 5	CAT9240310	(4x(2x0.15))C	7.5	12.5
3 3	CAT9240450	(4x(2x0.15))C	7.5	12.5
3 4	CAT9240490	(4x(2x0.15))C	7.5	12.5
3 5	CAT9240410	(4x(2x0.15))C	7.5	12.5
4 4	CAT9240470	(4x(2x0.15))C	7.5	12.5
4 5	CAT9240430	(4x(2x0.15))C	7.5	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed with these connectors				
Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
L angle curve lower	L angle curve upper	T angle curve outer	T angle curve inner	straight
				

Harnessed Ethernet cables | CAT5e
PUR-ROBOT with Hirose connectors

* Technical information on the cable quality:
PUR-ROBOT
Page 398

Harnessed Ethernet cables, CAT5e, PUR-ROBOT, with Hirose connectors, 8-pole, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Straight				
1 2	CAT9440380	4x(2x0.15)C	9.5	10
1 3	CAT9440540	4x(2x0.15)C	9.5	10
1 4	CAT9440560	4x(2x0.15)C	9.5	10
1 5	CAT9440320	4x(2x0.15)C	9.5	10
2 1	CAT9440360	4x(2x0.15)C	9.5	10
2 2	CAT9440340	4x(2x0.15)C	9.5	10
2 3	CAT9440500	4x(2x0.15)C	9.5	10
2 4	CAT9440520	4x(2x0.15)C	9.5	10
2 5	CAT9440300	4x(2x0.15)C	9.5	10
3 3	CAT9440440	4x(2x0.15)C	9.5	10
3 4	CAT9440480	4x(2x0.15)C	9.5	10
3 5	CAT9440400	4x(2x0.15)C	9.5	10
4 4	CAT9440460	4x(2x0.15)C	9.5	10
4 5	CAT9440420	4x(2x0.15)C	9.5	10
Crossover				
1 2	CAT9440390	4x(2x0.15)C	9.5	10
1 3	CAT9440550	4x(2x0.15)C	9.5	10
1 4	CAT9440570	4x(2x0.15)C	9.5	10
1 5	CAT9440330	4x(2x0.15)C	9.5	10
2 1	CAT9440370	4x(2x0.15)C	9.5	10
2 2	CAT9440350	4x(2x0.15)C	9.5	10
2 3	CAT9440510	4x(2x0.15)C	9.5	10
2 4	CAT9440530	4x(2x0.15)C	9.5	10
2 5	CAT9440310	4x(2x0.15)C	9.5	10
3 3	CAT9440450	4x(2x0.15)C	9.5	10
3 4	CAT9440490	4x(2x0.15)C	9.5	10
3 5	CAT9440410	4x(2x0.15)C	9.5	10
4 4	CAT9440470	4x(2x0.15)C	9.5	10
4 5	CAT9440430	4x(2x0.15)C	9.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed with these connectors				
Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
L angle curve lower	L angle curve upper	T angle curve outer	T angle curve inner	straight
				

Harnessed Ethernet cables | CAT5e
TPE with Hirose connectors

* Technical information on the cable quality:
TPE
Page 196

Harnessed Ethernet cables, CAT5e, TPE, with Hirose connectors, 8-pole, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Straight				
1 2	CAT9040380	(4x(2x0.15))C	8.5	10
1 3	CAT9040540	(4x(2x0.15))C	8.5	10
1 4	CAT9040560	(4x(2x0.15))C	8.5	10
1 5	CAT9040320	(4x(2x0.15))C	8.5	10
2 1	CAT9040360	(4x(2x0.15))C	8.5	10
2 2	CAT9040340	(4x(2x0.15))C	8.5	10
2 3	CAT9040500	(4x(2x0.15))C	8.5	10
2 4	CAT9040520	(4x(2x0.15))C	8.5	10
2 5	CAT9040300	(4x(2x0.15))C	8.5	10
3 3	CAT9040440	(4x(2x0.15))C	8.5	10
3 4	CAT9040480	(4x(2x0.15))C	8.5	10
3 5	CAT9040400	(4x(2x0.15))C	8.5	10
4 4	CAT9040460	(4x(2x0.15))C	8.5	10
4 5	CAT9040420	(4x(2x0.15))C	8.5	10
Crossover				
1 2	CAT9040390	(4x(2x0.15))C	8.5	10
1 3	CAT9040550	(4x(2x0.15))C	8.5	10
1 4	CAT9040570	(4x(2x0.15))C	8.5	10
1 5	CAT9040330	(4x(2x0.15))C	8.5	10
2 1	CAT9040370	(4x(2x0.15))C	8.5	10
2 2	CAT9040350	(4x(2x0.15))C	8.5	10
2 3	CAT9040510	(4x(2x0.15))C	8.5	10
2 4	CAT9040530	(4x(2x0.15))C	8.5	10
2 5	CAT9040310	(4x(2x0.15))C	8.5	10
3 3	CAT9040450	(4x(2x0.15))C	8.5	10
3 4	CAT9040490	(4x(2x0.15))C	8.5	10
3 5	CAT9040410	(4x(2x0.15))C	8.5	10
4 4	CAT9040470	(4x(2x0.15))C	8.5	10
4 5	CAT9040430	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed with these connectors				
Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
L angle curve lower	L angle curve upper	T angle curve outer	T angle curve inner	straight
				

Harnessed Ethernet cables | CAT6

* Technical information on the cable quality:

PVC, oil-res.	PUR	TPE
Page 184	Page 192	Page 196

Harnessed Ethernet cables, CAT6, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 (CAT6A) 				
PVC, oil-res.	CAT9331002	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431002	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531002	(4x(2x0.15))C	8.5	10
Harting RJ45 (CAT6A)/ Harting RJ45 (CAT6A) 				
PVC, oil-res.	CAT9331003	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431003	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531003	(4x(2x0.15))C	8.5	10
Telegärtner RJ45 (CAT6)/ Telegärtner RJ45 (CAT6) 				
PVC, oil-res.	CAT9331004	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431004	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531004	(4x(2x0.15))C	8.5	10
Telegärtner RJ45 (CAT6)/ Telegärtner M12 x-coded 				
PVC, oil-res.	CAT9331005	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431005	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531005	(4x(2x0.15))C	8.5	10
Telegärtner RJ45 (CAT6)/ Telegärtner RJ45 angled (CAT6A) 				
PVC, oil-res.	CAT9331006	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431006	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531006	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT6

* Technical information on the cable quality:

PVC, oil-res.	PUR	TPE
Page 184	Page 192	Page 196

Harnessed Ethernet cables, CAT6, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Phoenix Contact RJ45 (CAT6A)/ Phoenix Contact RJ45 (CAT6A) 				
PVC, oil-res.	CAT9331009	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431009	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531009	(4x(2x0.15))C	8.5	10
Phoenix Contact M12 x-coded (CAT6A)/ Phoenix Contact M12 x-coded (CAT6A) 				
PVC, oil-res.	CAT9331012	(4x(2x0.15))C	7.5	12.5
PUR	CAT9431012	(4x(2x0.15))C	7.5	12.5
TPE	CAT9531012	(4x(2x0.15))C	8.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT6

* Technical information on the cable quality:

TPE

Page 196

Harnessed Ethernet cables, CAT6, 8-pole, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Straight				
Hirose RJ45 (CAT6A)/ Hirose RJ45 (CAT6A)				
TPE	CAT9040600	(4x(2x0.15)C)C	10.5	12.5
Metz RJ45 E-DAT IP67/ Metz RJ45 E-DAT IP67				
TPE	CAT9040640	(4x(2x0.15)C)C	10.5	12.5
Harting Han3A RJ45 (CAT6)/ Harting Han3A RJ45 (CAT6)				
TPE	CAT9040680	(4x(2x0.15)C)C	10.5	12.5
Crossover				
Hirose RJ45 (CAT6A)/ Hirose RJ45 (CAT6A)				
TPE	CAT9040620	(4x(2x0.15)C)C	10.5	12.5
Metz RJ45 E-DAT IP67/ Metz RJ45 E-DAT IP67				
TPE	CAT9040660	(4x(2x0.15)C)C	10.5	12.5
Harting Han3A RJ45 (CAT6)/ Harting Han3A RJ45 (CAT6)				
TPE	CAT9040700	(4x(2x0.15)C)C	10.5	12.5
M12 x-coded				
Telegärtner M12 x-coded (CAT6A)/ Telegärtner M12 x-coded (CAT6A)				
TPE	CAT9040720	(4x(2x0.15)C)C	10.5	12.5
Telegärtner M12 x-coded (CAT6A)/ open cable end				
TPE	CAT9040760	(4x(2x0.15)C)C	10.5	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT6A

* Technical information on the cable quality:

PVC, oil-res.

PUR

PUR-ROBOT

TPE

Page 184

Page 192

Page 398

Page 196

Harnessed Ethernet cables, CAT6A, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 (CAT6A)				
PUR-ROBOT	CAT9641001	4x(2x0.15)C	10.5	10
TPE	CAT9541001	(4x(2x0.15)C)C	10.5	12.5
Harting RJ45 (CAT6A)/ Harting RJ45 (CAT6A)				
PUR-ROBOT	CAT9641002	4x(2x0.15)C	10.5	10
TPE	CAT9541002	(4x(2x0.15)C)C	10.5	12.5
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 (CAT6A)				
PVC, oil-res.	CAT9341016	4x(2x0.20)C	10.0	12.5
PUR	CAT9441016	4x(2x0.20)C	10.0	12.5
PUR-ROBOT	CAT9641015	4x(2x0.15)C	10.5	10
TPE	CAT9541015	(4x(2x0.15)C)C	10.5	12.5
Telegärtner RJ45 (CAT6A)/ Telegärtner M12 x-coded				
PVC, oil-res.	CAT9341017	4x(2x0.20)C	10.0	12.5
PUR	CAT9441017	4x(2x0.20)C	10.0	12.5
PUR-ROBOT	CAT9641016	4x(2x0.15)C	10.5	10
TPE	CAT9541016	(4x(2x0.15)C)C	10.5	12.5
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 angled (CAT6A)				
PVC, oil-res.	CAT9341018	4x(2x0.20)C	10.0	12.5
PUR	CAT9441018	4x(2x0.20)C	10.0	12.5
PUR-ROBOT	CAT9641017	4x(2x0.15)C	10.5	10
TPE	CAT9541017	(4x(2x0.15)C)C	10.5	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT6A

* Technical information on the cable quality:

PVC, oil-res.	PUR	PUR-ROBOT	TPE
Page 184	Page 192	Page 398	Page 196

Harnessed Ethernet cables, CAT6A, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Phoenix Contact M12 x-coded (CAT6A)/ Phoenix Contact M12 x-coded (CAT6A) 				
PVC, oil-res.	CAT9341010	4x(2x0.20)C	10.0	12.5
PUR	CAT9441010	4x(2x0.20)C	10.0	12.5
PUR-ROBOT	CAT9641009	4x(2x0.15)C	10.5	10
TPE	CAT9541009	(4x(2x0.15)C)C	10.5	12.5
Harting M12 x-coded Socket (CAT6A)/ Harting M12 x-coded Pin (CAT6A) 				
PVC, oil-res.	CAT9341019	4x(2x0.20)C	10.0	12.5
PUR	CAT9441019	4x(2x0.20)C	10.0	12.5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Ethernet cables | CAT7

* Technical information on the cable quality:

PUR-ROBOT	TPE
Page 398	Page 196

Harnessed Ethernet cables, CAT7, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 (CAT6A) 				
PUR-ROBOT	CAT9651002	4x(2x0.15)C	10.5	10
TPE	CAT9551002	(4x(2x0.15)C)C	10.5	12.5
Harting RJ45 (CAT6A)/ Harting RJ45 (CAT6A) 				
PUR-ROBOT	CAT9651003	4x(2x0.15)C	10.5	10
TPE	CAT9551003 ¹⁾	(4x(2x0.15)C)C	10.5	12.5
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 (CAT6A) 				
PUR-ROBOT	CAT9651004	4x(2x0.15)C	10.5	10
TPE	CAT9551004	(4x(2x0.15)C)C	10.5	12.5
Telegärtner RJ45 (CAT6A)/ Telegärtner RJ45 angled (CAT6A) 				
PUR-ROBOT	CAT9651005	4x(2x0.15)C	10.5	10
TPE	CAT9551005	(4x(2x0.15)C)C	10.5	12.5
Phoenix Contact M12 x-coded (CAT6A)/ Phoenix Contact M12 x-coded (CAT6A) 				
PUR-ROBOT	CAT9651009	4x(2x0.15)C	10.5	10
TPE	CAT9551009	(4x(2x0.15)C)C	10.5	12.5
Dätwyler Module PS-TERA (CAT7A)/ Dätwyler Connector PS-TERA (CAT7A) 				
PUR-ROBOT	CAT9651010	4x(2x0.15)C	10.5	10
TPE	CAT9551010	(4x(2x0.15)C)C	10.5	12.5
Dätwyler Module PS-TERA (CAT7A)/ Dätwyler Connector PS-TERA (CAT7A) 				
PUR-ROBOT	CAT9651011	4x(2x0.15)C	10.5	10
TPE	CAT9551011	(4x(2x0.15)C)C	10.5	12.5

¹⁾ This cable must be stripped before the connector and covered with a shrink-on tube so that the patch plug can be fitted.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends►TIA56A
Harnessing one end RJ45/one end M12 x-coded►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Industrial Ethernet
moulded

* Technical information on the cable quality:

PVC, oil-res. PUR
Page 184 Page 192

Industrial Ethernet moulded, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
M8 cable socket/ M8 cable connector 				
PVC, oil-res.	MAT904125450	(4x0.25)C	6.5	12.5
PUR	MAT904125410	(4x0.25)C	6.5	12.5
M8 cable connector/ M8 cable connector 				
PVC, oil-res.	MAT904125451	(4x0.25)C	6.5	12.5
PUR	MAT904125411	(4x0.25)C	6.5	12.5
M8 angled socket/ open cable end 				
PVC, oil-res.	MAT904125452	(4x0.25)C	6.5	12.5
PUR	MAT904125412	(4x0.25)C	6.5	12.5
M8 cable socket/ RJ45 straight 				
PVC, oil-res.	MAT904125453	(4x0.25)C	6.5	12.5
PUR	MAT904125413	(4x0.25)C	6.5	12.5
M12 cable connector d-coded/ M12 cable connector d-coded 				
PVC, oil-res.	MAT904125454	(4x0.25)C	6.5	12.5
PUR	MAT904125414	(4x0.25)C	6.5	12.5
M12 angled connector d-coded Pin/ open cable end 				
PVC, oil-res.	MAT904125455	(4x0.25)C	6.5	12.5
PUR	MAT904125415	(4x0.25)C	6.5	12.5
M12 cable connector d-coded/ open cable end 				
PVC, oil-res.	MAT904125456	(4x0.25)C	6.5	12.5
PUR	MAT904125416	(4x0.25)C	6.5	12.5

Special production cables ► delivery time upon request
Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing **RJ45 at both ends ► TIA56A**
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915



Industrial Ethernet
moulded

* Technical information on the cable quality:

PVC, oil-res. PUR
Page 184 Page 192

Industrial Ethernet moulded, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
M12 cable connector d-coded/ RJ45 straight 				
PVC, oil-res.	MAT904125457	(4x0.25)C	6.5	12.5
PUR	MAT904125417	(4x0.25)C	6.5	12.5
M12 angled connector d-coded RJ45 straight 				
PVC, oil-res.	MAT904125458	(4x0.25)C	6.5	12.5
PUR	MAT904125418	(4x0.25)C	6.5	12.5
M12 cable connector d-coded/ M8 cable connector 				
PVC, oil-res.	MAT904125459	(4x0.25)C	6.5	12.5
PUR	MAT904125419	(4x0.25)C	6.5	12.5
RJ45 straight/ RJ45 straight 				
PVC, oil-res.	MAT904125460	(4x0.25)C	6.5	12.5
PUR	MAT904125420	(4x0.25)C	6.5	12.5
RJ45 straight/ open cable end 				
PVC, oil-res.	MAT904125461	(4x0.25)C	6.5	12.5
PUR	MAT904125421	(4x0.25)C	6.5	12.5
M12 cable socket d-coded/ M12 cable connector d-coded 				
PVC, oil-res.	MAT904125462	(4x0.25)C	6.5	12.5
PUR	MAT904125422	(4x0.25)C	6.5	12.5
M12 cable socket d-coded/ M12 angled connector d-coded 				
PVC, oil-res.	MAT904125463	(4x0.25)C	6.5	12.5
PUR	MAT904125423	(4x0.25)C	6.5	12.5

Special production cables ► delivery time upon request
Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing **RJ45 at both ends ► TIA56A**
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Harnessed Profibus cables | PVC

* Technical information on the cable quality:
PVC, oil-res.
Page 184

Harnessed Profibus cables, PVC, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
1 1	BUS9041004	(2x0.25)C	8.5	12.5
1 2	BUS9041001	(2x0.25)C	8.5	12.5
1 5	BUS9041011	(2x0.25)C	8.5	12.5
1 6	BUS9041006	(2x0.25)C	8.5	12.5
1 13	BUS9041005	(2x0.25)C	8.5	12.5
2 2	BUS9041002	(2x0.25)C	8.5	12.5
2 5	BUS9041013	(2x0.25)C	8.5	12.5
2 6	BUS9041007	(2x0.25)C	8.5	12.5
2 7	BUS9041054	(2x0.25)C	8.5	12.5
2 8	BUS9041059	(2x0.25)C	8.5	12.5
2 9	BUS9041062	(2x0.25)C	8.5	12.5
2 10	BUS9041055	(2x0.25)C	8.5	12.5
2 13	BUS9041003	(2x0.25)C	8.5	12.5
3 4	BUS9041066	(2x0.25)C	8.5	12.5
3 13	BUS9041064	(2x0.25)C	8.5	12.5
4 13	BUS9041065	(2x0.25)C	8.5	12.5
5 5	BUS9041014	(2x0.25)C	8.5	12.5
5 6	BUS9041010	(2x0.25)C	8.5	12.5
5 13	BUS9041012	(2x0.25)C	8.5	12.5
6 6	BUS9041009	(2x0.25)C	8.5	12.5
6 13	BUS9041008	(2x0.25)C	8.5	12.5
7 2	BUS9041053 ¹⁾	(2x0.25)C	8.5	12.5
7 13	BUS9041056	(2x0.25)C	8.5	12.5
8 2	BUS9041061 ¹⁾	(2x0.25)C	8.5	12.5
9 2	BUS9041060 ¹⁾	(2x0.25)C	8.5	12.5
9 13	BUS9041063	(2x0.25)C	8.5	12.5
10 2	BUS9041052 ¹⁾	(2x0.25)C	8.5	12.5
10 13	BUS9041057	(2x0.25)C	8.5	12.5
11 13	BUS9041058 ¹⁾	(2x0.25)C	8.5	12.5
12 2	BUS9041051 ¹⁾	(2x0.25)C	8.5	12.5

¹⁾For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
M12, 5 poles, Socket, straight	M12, 5 poles, Pin, straight	M12, 5 poles, Pin, angled	M12, 5 poles, Socket, angled	M12, 5 poles, Socket, angled
				
Connector 6	Connector 7	Connector 8	Connector 9	Connector 10
M12, 5 poles, Pin, angled	SUB-D, 9 poles, Pin, straight	SUB-D, 9 poles, Pin, end plug, 90°	SUB-D, 9 poles, Pin, 45°, IP67	SUB-D, 9 poles, Pin, end plug, 45°
				
Connector 11	Connector 12	Connector 13		
SUB-D, 9 poles, Socket/Pin, pass, angled 45°	SUB-D, 9 poles, Socket/Pin, pass, angled 90°	open cable end		
				

* For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Harnessed Profibus cables | PUR

* Technical information on the cable quality:
PUR
Page 192

Harnessed Profibus cables, PUR, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
1 1	BUS9041104	(2x0.25)C	8.5	12.5
1 2	BUS9041101	(2x0.25)C	8.5	12.5
1 5	BUS9041111	(2x0.25)C	8.5	12.5
1 6	BUS9041106	(2x0.25)C	8.5	12.5
1 13	BUS9041105	(2x0.25)C	8.5	12.5
2 2	BUS9041102	(2x0.25)C	8.5	12.5
2 5	BUS9041113	(2x0.25)C	8.5	12.5
2 6	BUS9041107	(2x0.25)C	8.5	12.5
2 7	BUS9041154	(2x0.25)C	8.5	12.5
2 8	BUS9041159	(2x0.25)C	8.5	12.5
2 9	BUS9041162	(2x0.25)C	8.5	12.5
2 10	BUS9041155	(2x0.25)C	8.5	12.5
2 13	BUS9041103	(2x0.25)C	8.5	12.5
3 4	BUS9041166	(2x0.25)C	8.5	12.5
3 13	BUS9041164	(2x0.25)C	8.5	12.5
4 13	BUS9041165	(2x0.25)C	8.5	12.5
5 5	BUS9041114	(2x0.25)C	8.5	12.5
5 6	BUS9041110	(2x0.25)C	8.5	12.5
5 13	BUS9041112	(2x0.25)C	8.5	12.5
6 6	BUS9041109	(2x0.25)C	8.5	12.5
6 13	BUS9041108	(2x0.25)C	8.5	12.5
7 2	BUS9041153 ¹⁾	(2x0.25)C	8.5	12.5
7 13	BUS9041156	(2x0.25)C	8.5	12.5
8 2	BUS9041161 ¹⁾	(2x0.25)C	8.5	12.5
9 2	BUS9041160 ¹⁾	(2x0.25)C	8.5	12.5
9 13	BUS9041163	(2x0.25)C	8.5	12.5
10 2	BUS9041152 ¹⁾	(2x0.25)C	8.5	12.5
10 13	BUS9041157	(2x0.25)C	8.5	12.5
11 13	BUS9041158 ¹⁾	(2x0.25)C	8.5	12.5
12 2	BUS9041151 ¹⁾	(2x0.25)C	8.5	12.5

¹⁾For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
M12, 5 poles, Socket, straight	M12, 5 poles, Pin, straight	M12, 5 poles, Pin, angled	M12, 5 poles, Socket, angled	M12, 5 poles, Socket, angled
				
Connector 6	Connector 7	Connector 8	Connector 9	Connector 10
M12, 5 poles, Pin, angled	SUB-D, 9 poles, Pin, straight	SUB-D, 9 poles, Pin, end plug, 90°	SUB-D, 9 poles, Pin, 45°, IP67	SUB-D, 9 poles, Pin, end plug, 45°
				
Connector 11	Connector 12	Connector 13		
SUB-D, 9 poles, Socket/Pin, pass, angled 45°	SUB-D, 9 poles, Socket/Pin, pass, angled 90°	open cable end		
				

* For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Harnessed Profibus cables | TPE

* Technical information on the cable quality:

TPE

Page 196

Harnessed Profibus cables, TPE, to your required length				
Harnessing with con- nector combination	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
1 1	BUS9041204	(2x0.25)C	9.0	10
1 2	BUS9041201	(2x0.25)C	9.0	10
1 5	BUS9041211	(2x0.25)C	9.0	10
1 6	BUS9041206	(2x0.25)C	9.0	10
1 13	BUS9041205	(2x0.25)C	9.0	10
2 2	BUS9041202	(2x0.25)C	9.0	10
2 5	BUS9041213	(2x0.25)C	9.0	10
2 6	BUS9041207	(2x0.25)C	9.0	10
2 7	BUS9041254	(2x0.25)C	9.0	10
2 8	BUS9041259	(2x0.25)C	9.0	10
2 9	BUS9041262	(2x0.25)C	9.0	10
2 10	BUS9041255	(2x0.25)C	9.0	10
2 13	BUS9041203	(2x0.25)C	9.0	10
3 4	BUS9041266	(2x0.25)C	9.0	10
3 13	BUS9041264	(2x0.25)C	9.0	10
4 13	BUS9041265	(2x0.25)C	9.0	10
5 5	BUS9041214	(2x0.25)C	9.0	10
5 6	BUS9041210	(2x0.25)C	9.0	10
5 13	BUS9041212	(2x0.25)C	9.0	10
6 6	BUS9041209	(2x0.25)C	9.0	10
6 13	BUS9041208	(2x0.25)C	9.0	10
7 2	BUS9041253 ¹⁾	(2x0.25)C	9.0	10
7 13	BUS9041256	(2x0.25)C	9.0	10
8 2	BUS9041261 ¹⁾	(2x0.25)C	9.0	10
9 2	BUS9041260 ¹⁾	(2x0.25)C	9.0	10
9 13	BUS9041263	(2x0.25)C	9.0	10
10 2	BUS9041252 ¹⁾	(2x0.25)C	9.0	10
10 13	BUS9041257	(2x0.25)C	9.0	10
11 13	BUS9041258 ¹⁾	(2x0.25)C	9.0	10
12 2	BUS9041251 ¹⁾	(2x0.25)C	9.0	10

¹⁾For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Connector 1	Connector 2	Connector 3	Connector 4	Connector 5
M12, 5 poles, Socket, straight	M12, 5 poles, Pin, straight	M12, 5 poles, Pin, angled	M12, 5 poles, Socket, angled	M12, 5 poles, Socket, angled
				
Connector 6	Connector 7	Connector 8	Connector 9	Connector 10
M12, 5 poles, Pin, angled	SUB-D, 9 poles, Pin, straight	SUB-D, 9 poles, Pin, end plug, 90°	SUB-D, 9 poles, Pin, 45°, IP67	SUB-D, 9 poles, Pin, end plug, 45°
				
Connector 11	Connector 12	Connector 13		
SUB-D, 9 poles, Socket/Pin, pass, angled 45°	SUB-D, 9 poles, Socket/Pin, pass, angled 90°	open cable end		
				

* For connectors with IN and OUT connection, the connection is always made on the IN side when the cable is connected. Other configurations upon request.

Harnessed Profinet cables

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 196

Harnessed Profinet cables, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Yamaichi RJ45 (Profinet)/ Yamaichi RJ45 (Profinet) 				
PVC	CAT9161001	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361001	(4x0.38)C	7.0	12.5
iguPUR	CAT9261001	(4x0.34)C	7.0	15
PUR	CAT9461001	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661001	(2x(2x0.34))C	8.5	10
TPE	CAT9561001	(4x0.38)C	7.5	10
Harting Han3A RJ45 (Profinet)/ Harting Han3A RJ45 (Profinet) 				
PVC	CAT9161002	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361002	(4x0.38)C	7.0	12.5
iguPUR	CAT9261002	(4x0.34)C	7.0	15
PUR	CAT9461002	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661002	(2x(2x0.34))C	8.5	10
TPE	CAT9561002	(4x0.38)C	7.5	10
Harting RJ45 (Profinet)/ Harting RJ45 (Profinet) 				
PVC	CAT9161003	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361003	(4x0.38)C	7.0	12.5
iguPUR	CAT9261003	(4x0.34)C	7.0	15
PUR	CAT9461003	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661003	(2x(2x0.34))C	8.5	10
TPE	CAT9561003	(4x0.38)C	7.5	10
Telegärtner RJ45 (Profinet)/ Telegärtner RJ45 (Profinet) 				
PVC	CAT9161004	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361004	(4x0.38)C	7.0	12.5
iguPUR	CAT9261004	(4x0.34)C	7.0	15
PUR	CAT9461004	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661004	(2x(2x0.34))C	8.5	10
TPE	CAT9561004	(4x0.38)C	7.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Profinet cables

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 196

Harnessed Profinet cables, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
Telegärtner RJ45 (Profinet)/ Telegärtner RJ45 (Profinet) 				
PVC	CAT9161005	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361005	(4x0.38)C	7.0	12.5
iguPUR	CAT9261005	(4x0.34)C	7.0	15
PUR	CAT9461005	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661005	(2x(2x0.34))C	8.5	10
TPE	CAT9561005	(4x0.38)C	7.5	10
Telegärtner RJ45 (Profinet)/ Telegärtner M12 x-coded (Profinet) 				
PVC	CAT9161006	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361006	(4x0.38)C	7.0	12.5
iguPUR	CAT9261006	(4x0.34)C	7.0	15
PUR	CAT9461006	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661006	(2x(2x0.34))C	8.5	10
TPE	CAT9561006	(4x0.38)C	7.5	10
Telegärtner M12 x-coded (Profinet)/ Telegärtner M12 x-coded (Profinet) 				
PVC	CAT9161007	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361007	(4x0.38)C	7.0	12.5
iguPUR	CAT9261007	(4x0.34)C	7.0	15
PUR	CAT9461007	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661007	(2x(2x0.34))C	8.5	10
TPE	CAT9561007	(4x0.38)C	7.5	10
Telegärtner RJ45 (Profinet)/ Binder M12 d-coded (Profinet) 				
PVC	CAT9161008	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361008	(4x0.38)C	7.0	12.5
iguPUR	CAT9261008	(4x0.34)C	7.0	15
PUR	CAT9461008	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661008	(2x(2x0.34))C	8.5	10
TPE	CAT9561008	(4x0.38)C	7.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Profinet cables

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 196

Harnessed Profinet cables, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
				
PVC	CAT9161009	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361009	(4x0.38)C	7.0	12.5
iguPUR	CAT9261009	(4x0.34)C	7.0	15
PUR	CAT9461009	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661009	(2x(2x0.34))C	8.5	10
TPE	CAT9561009	(4x0.38)C	7.5	10
				
PVC	CAT9161012	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361012	(4x0.38)C	7.0	12.5
iguPUR	CAT9261012	(4x0.34)C	7.0	15
PUR	CAT9461012	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661012	(2x(2x0.34))C	8.5	10
TPE	CAT9561012	(4x0.38)C	7.5	10
				
PVC	CAT9161014	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361014	(4x0.38)C	7.0	12.5
iguPUR	CAT9261014	(4x0.34)C	7.0	15
PUR	CAT9461014	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661014	(2x(2x0.34))C	8.5	10
TPE	CAT9561014	(4x0.38)C	7.5	10
				
PVC	CAT9161015	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361015	(4x0.38)C	7.0	12.5
iguPUR	CAT9261015	(4x0.34)C	7.0	15
PUR	CAT9461015	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661015	(2x(2x0.34))C	8.5	10
TPE	CAT9561015	(4x0.38)C	7.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Profinet cables

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 196

Harnessed Profinet cables, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
				
PVC	CAT9161016	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361016	(4x0.38)C	7.0	12.5
iguPUR	CAT9261016	(4x0.34)C	7.0	15
PUR	CAT9461016	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661016	(2x(2x0.34))C	8.5	10
TPE	CAT9561016	(4x0.38)C	7.5	10
				
PVC	CAT9161017	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361017	(4x0.38)C	7.0	12.5
iguPUR	CAT9261017	(4x0.34)C	7.0	15
PUR	CAT9461017	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661017	(2x(2x0.34))C	8.5	10
TPE	CAT9561017	(4x0.38)C	7.5	10
				
PVC	CAT9161018	(4x0.34)C	7.0	15
PVC, oil-res.	CAT9361018	(4x0.38)C	7.0	12.5
iguPUR	CAT9261018	(4x0.34)C	7.0	15
PUR	CAT9461018	(4x0.38)C	7.0	12.5
PUR-ROBOT	CAT9661018	(2x(2x0.34))C	8.5	10
TPE	CAT9561018	(4x0.38)C	7.5	10

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ▶ TIA56A
Harnessing one end RJ45/one end M12 x-coded ▶ TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ▶ Page 915

Harnessed Profinet cables

* Technical information on the cable quality:

PVC	PVC, oil-res.	iguPUR	PUR	PUR-ROBOT	TPE
Page 180	Page 184	Page 188	Page 192	Page 398	Page 196

Harnessed Profinet cables with moulded M12 connectors, in fixed lengths					
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]	Cable length [m]
M12 cable connector d-coded/ M12 cable connector d-coded					
PVC, oil-res.	BUS9041070	(4x0.38)C	7.0	12.5	3
PVC, oil-res.	BUS9041071	(4x0.38)C	7.0	12.5	5
PUR	BUS9041170	(4x0.38)C	7.0	12.5	3
PUR	BUS9041171	(4x0.38)C	7.0	12.5	5
TPE	BUS9041270	(4x0.38)C	7.5	10	3
TPE	BUS9041271	(4x0.38)C	7.5	10	5
M12 cable connector d-coded/ open cable end					
PVC, oil-res.	BUS9041072	(4x0.38)C	7.0	12.5	3
PVC, oil-res.	BUS9041073	(4x0.38)C	7.0	12.5	5
PUR	BUS9041172	(4x0.38)C	7.0	12.5	3
PUR	BUS9041173	(4x0.38)C	7.0	12.5	5
TPE	BUS9041272	(4x0.38)C	7.5	10	3
TPE	BUS9041273	(4x0.38)C	7.5	10	5

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing **RJ45 at both ends**►TIA56A
Harnessing **one end RJ45/one end M12 x-coded**►TIA56B
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915



Industrial Profinet cables
with moulded connectors

* Technical information on the cable quality:

PVC, oil-res. PUR
Page 184 Page 192

Industrial Profinet moulded, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
M8 cable socket/ M8 cable connector				
PVC, oil-res.	MAT904125470	(4x0.38)C	7.0	12.5
PUR	MAT904125430	(4x0.38)C	7.0	12.5
M8 cable connector/ M8 cable connector				
PVC, oil-res.	MAT904125471	(4x0.38)C	7.0	12.5
PUR	MAT904125431	(4x0.38)C	7.0	12.5
M8 angle socket/ open cable end				
PVC, oil-res.	MAT904125472	(4x0.38)C	7.0	12.5
PUR	MAT904125432	(4x0.38)C	7.0	12.5
M8 cable socket/ RJ45 straight				
PVC, oil-res.	MAT904125473	(4x0.38)C	7.0	12.5
PUR	MAT904125433	(4x0.38)C	7.0	12.5
M12 cable connector d-coded/ M12 cable connector d-coded				
PVC, oil-res.	MAT904125474	(4x0.38)C	7.0	12.5
PUR	MAT904125434	(4x0.38)C	7.0	12.5
M12 angled connector d-coded/ open cable end				
PVC, oil-res.	MAT904125475	(4x0.38)C	7.0	12.5
PUR	MAT904125435	(4x0.38)C	7.0	12.5
M12 cable connector d-coded/ open cable end				
PVC, oil-res.	MAT904125476	(4x0.38)C	7.0	12.5
PUR	MAT904125436	(4x0.38)C	7.0	12.5

Special production cables ► delivery time upon request
Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ► TIA56A
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

Industrial Profinet cables
moulded

* Technical information on the cable quality:

PVC, oil-res. PUR
Page 184 Page 192

Industrial Profinet moulded, to your required length				
Cable quality	Part No.	Number of cores and conductor nominal cross section [mm²]	Ø [mm]	Bend radius [x d]
M12 cable connector d-coded/ RJ45 straight				
PVC, oil-res.	MAT904125477	(4x0.38)C	7.0	12.5
PUR	MAT904125437	(4x0.38)C	7.0	12.5
M12 angled connector d-coded RJ45 straight				
PVC, oil-res.	MAT904125478	(4x0.38)C	7.0	12.5
PUR	MAT904125438	(4x0.38)C	7.0	12.5
M12 cable connector d-coded/ M8 cable connector				
PVC, oil-res.	MAT904125479	(4x0.38)C	7.0	12.5
PUR	MAT904125439	(4x0.38)C	7.0	12.5
RJ45 straight/ RJ45 straight				
PVC, oil-res.	MAT904125480	(4x0.38)C	7.0	12.5
PUR	MAT904125440	(4x0.38)C	7.0	12.5
RJ45 straight/ open cable end				
PVC, oil-res.	MAT904125481	(4x0.38)C	7.0	12.5
PUR	MAT904125441	(4x0.38)C	7.0	12.5
M12 cable socket d-coded/ M12 cable connector d-coded				
PVC, oil-res.	MAT904125482	(4x0.38)C	7.0	12.5
PUR	MAT904125442	(4x0.38)C	7.0	12.5
M12 cable socket d-coded/ M12 angled connector d-coded				
PVC, oil-res.	MAT904125483	(4x0.38)C	7.0	12.5
PUR	MAT904125443	(4x0.38)C	7.0	12.5

Special production cables ► delivery time upon request
Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core
Harnessing RJ45 at both ends ► TIA56A
igus® GmbH defines cable length as entire length including connectors or open harnessing. ► Page 915

		igus® Part No.	Manufacturer	Cable diameter mm	Protection class	Number of contacts	Connection method	Bus type	Conductor cross section [mm²]	Cable quality	matching chain- flex® cables	Maximum cable diameter mm	Number of cores and conductor nominal cross section
		MAT01717352	HARTING	4.5-9.0	IP20	8	Cutting clamps	CAT6	0.14-0.34	PVC	CFBUS.PVC.049	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049	7.5	(4x(2x0.15))C
										TPE	CFBUS.049	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.049	8.5	4x(2x0.14)C
		MAT01713662	HARTING	6.0-6.9	IP20	8	Hand tool needed	CAT6	0.09-0.25	PVC	CFBUS.PVC.049*	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049*	7.5	(4x(2x0.15))C
		MAT0176869	Phoenix Contact	4.5-8.0	IP20	8	Cutting clamps	CAT5e	0.14-0.25	PVC	CF888.045	7.5	(4x(2x0.15))C
										PVC	CFBUS.PVC.045	7.5	(4x(2x0.15))C
										iguPUR	CF898.045	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.045	7.5	(4x(2x0.15))C
										TPE	CFBUS.045*	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.045*	8.5	4x(2x0.14)C
		MAT01733149	Telegärtner	5.5-7.3	IP20	8	Hand tool needed	CAT6A CAT6	0.14-0.25	TPE	CFBUS.050*	10.5	4x(2x0.15)C)C
										PUR-Robot	CFROBOT8.050*	10.5	4x(2x0.15)C
		MAT01733150	Telegärtner	max. 7.0	IP20	-	-	-	-	PVC	CFBUS.PVC.049	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049	7.5	(4x(2x0.15))C
										TPE	CFBUS.049*	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.049*	8.5	4x(2x0.14)C
		MAT0176370	Yamaichi	-	IP20	8	Hand tool needed	CAT6	0.14-0.25	PVC	CFBUS.PVC.049	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049	7.5	(4x(2x0.15))C
		MAT0176371	Yamaichi	max. 7.5	IP20	-	-	-	-	TPE	CFBUS.049*	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.049*	8.5	4x(2x0.14)C
		MAT01717477	WEIDMÜLLER	5.5-8.5	IP20	8	Cutting clamps	Cat.6 (CAT6A acc. to data sheet)	0.14-0.34	PVC	CFBUS.PVC.049	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049	7.5	(4x(2x0.15))C
										TPE	CFBUS.049	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.049	8.5	4x(2x0.14)C
		MAT01730294	Telegärtner	5.5-10.0	IP20	8	Cutting clamps	CAT6A	0.14-0.34	PVC	CFBUS.PVC.050	9.5	4x(2x0.20)C
										PUR	CFBUS.PUR.050	9.5	4x(2x0.20)C
										TPE	CFBUS.050*	10.5	(4x(2x0.15)C)C
										PUR-Robot	CFROBOT8.050*	10.5	4x(2x0.15)C
		MAT0173509	HARTING	6.0-7.0	IP20	4	Cutting clamps	CAT5/ Profinet	0.14-0.34	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060*	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060*	8.5	(2x(2x0.34))C
										PVC	CFBUS.PVC.052*	9.5	(4x(2x0.15)C)C
		MAT01733547	Dätwyler	max. 8.9	IP20	8	Cutting clamps	CAT7A	0.15-0.34	PUR	CFBUS.PUR.052*	9.5	(4x(2x0.15)C)C
										TPE	CFBUS.052*	10.5	(4x(2x0.15)C)C
										PUR-Robot	CFROBOT8.052*	10.5	4x(2x0.15)C
										PVC	CFBUS.PVC.052*	9.5	(4x(2x0.15)C)C
		MAT01733548	Dätwyler	max. 6.3	IP20	8	Cutting clamps	CAT7A	0.15-0.34	PUR	CFBUS.PUR.052*	9.5	(4x(2x0.15)C)C
										TPE	CFBUS.052*	10.5	(4x(2x0.15)C)C
										PUR-Robot	CFROBOT8.052*	10.5	4x(2x0.15)C
										PVC	CF888.060	7	(4x0.38)C
		MAT0179875	Binder	6.0-8.0	IP67	4	Screw clamps	CAT5/ Profinet	max. 0.75	PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060*	8.5	(2x(2x0.34))C

All connectors are downward compatible. Please note the outer diameter of the cable and the conductor cross section.

* According to data sheet, the connectors do not match these cables but the cables can nevertheless be manually modified/tapered.

		igus® Part No.	Manufacturer	Cable diameter mm	Protection class	Number of contacts	Connection method	Bus type	Conductor cross section [mm²]	Cable quality	matching chain- flex® cables	Maximum ca- ble diameter mm	Number of cores and conductor nominal cross section
		Series 615 connector, socket	TE/Intercontec	4.5-10.5 (plastic clamp ring) 4.5-12mm (metal clamp ring)	IP67	12	Hand tool needed	CAT5e/ Profinet	0.05-0.75	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060*	8.5	(2x(2x0.34))C
		615 Coupling	TE/Intercontec	4.5-10.5 (plastic clamp ring) 4.5-12mm (metal clamp ring)	IP67	12	Hand tool needed	CAT5e/ Profinet	0.05-0.75	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060*	8.5	(2x(2x0.34))C
		MAT01733199	Phoenix Contact	5.0-9.7	IP67	8	Cutting clamps	CAT6A/ Ethernet	0.14-0.34	PVC	CFBUS.PVC.050	9.5	4x(2x0.20)C
										PUR	CFBUS.PUR.050	9.5	4x(2x0.20)C
										TPE	CFBUS.050*	10.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.050*	10.5	4x(2x0.15)C
		MAT01733200	Phoenix Contact	5.0-9.7	IP67	8	Cutting clamps	CAT6A/ Profinet	0.25-0.5	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060	8.5	(2x(2x0.34))C
		MAT01734849	Phoenix Contact	5.0-9.7	IP67	8	Cutting clamps	CAT6A/ Ethernet	0.14-0.34	PVC	CFBUS.PVC.050	9.5	4x(2x0.20)C
										PUR	CFBUS.PUR.050	9.5	4x(2x0.20)C
										TPE	CFBUS.050*	10.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.050*	10.5	4x(2x0.15)C
		MAT01735081	Phoenix Contact	5.0-9.7	IP67	8	Cutting clamps	CAT6A/ Profinet	0.25-0.5	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
										TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060	7.5	(4x0.38)C
										PUR-Robot	CFROBOT8.060	8.5	(2x(2x0.34))C
		MAT01716619	Siemens	6.5-6.5	IP20	4	Cutting clamps	CAT5/ Profinet	0.14-0.38	PVC	CF888.060	7	(4x0.38)C
										PVC	CFBUS.PVC.040	6.5	(4x0.25)C
										PVC	CFBUS.PVC.060	7	(4x0.38)C
										iguPUR	CF898.060	7	(4x0.38)C
										PUR	CFBUS.PUR.040	6.5	(4x0.25)C
										PUR	CFBUS.PUR.060	7	(4x0.38)C
		MAT01721074	Siemens	8.0-8.0	IP20	8	Cutting clamps	CAT6	0.14-0.25	TPE	CFBUS.040	7	(4x0.25)C
										TPE	CFBUS.060*	7.5	(4x0.38)C
										PVC	CFBUS.PVC.049	7.5	(4x(2x0.15))C
										PUR	CFBUS.PUR.049	7.5	(4x(2x0.15))C
										TPE	CFBUS.049*	8.5	(4x(2x0.15))C
										PUR-Robot	CFROBOT8.049*	8.5	4x(2x0.14)C

All connectors are downward compatible. Please note the outer diameter of the cable and the conductor cross section.

* According to data sheet, the connectors do not match these cables but the cables can nevertheless be manually modified/tapered.