HENNLICH s.r.o.

FOG CANNON HE50F

The HE50F cannon comes as a "turn key" solution complete with an in-build generator. It is a perfect unit for job sites lacking a convenient power source.

APPLICATIONS & INDUSTRIES

- Demolition & Construction
- Coal handling & Power generation
- Mining & Quarrying
- Bulk materials ports & Shipping
- Steel & Slag
- Waste Transfer
- Recycling & Scrap
- Wood Processing
- Desinfection spraying

BASIC MODEL INCLUDES

Rear mounted axial fan High-efficiency spray nozzles Central column support to enable horizontal rotation Booster pump Water filter, pressure gauge Electric control panel Road certified trailer Diesel generator Water tanks Additional pump to increase the inlet pressure

Additional pump to increase the inici pressure	
TECHNICAL SPECIFICATION	HE50F
Throw (meters)	up to 50 (still conditions)
Coverage (m ²)	approx. 2800
Droplet size (µm)	50-150
Booster pump (kW)	5,5
Fan (kW)	7,5
Horizontal rotation	0-350°
Adjustable vertical elevation	0-35°
Water consumption (l/h)	1556
Nozzles quantity (pcs)	36
Power supply (diesel engine)	38.0 kW, 3 x 400 V AC, 50 Hz
Run time for the engine (hrs)	8.30 (75% PRP)
Water bowser (I)	2 x 1000

